

The Concorde Series 2

Founded in fire and forged in history, Lexington Forge offers the tradition of fine craftsmanship and the convenience of contemporary technology in each of its uniquely beautiful stoves. Beyond its utilitarian uses for cooking and heating, fire has always been a gathering point at the hearth of every home. Create your own gathering space and add the beauty and classic warmth of a Lexington Forge to yours. It will spark your own traditions and new reasons for coming together. After all, it's never too late to forge your own history.



CSDV20D direct vent cast stove with double doors in Enamel Brown



CSDV30S direct vent cast stove with a single door in Enamel Black



CSDV40S direct vent cast iron stove with a single door in Enamel Sand

CAST IRON DIRECT VENT STOVES

The elegant castings of the Concorde direct vent stove are timeless in their design and complement any décor or setting. The intricate design and detailing will add character to any room. Designed with the latest direct-vent technology, this stove proves to be a clean burning, efficient heater and is easily installed into almost any room. Traditional styling combined with the warmth and ambiance of a fire make the Lexington Forge[®] direct vent gas stove a valued addition to your home. Our designers have meticulously scrutinized every detail to ensure that you receive the finest gas stove built today.

WHEN YOU CHOOSE A STATE-OF-THE-ART GAS APPLIANCE BY LEXINCTON FORGE, WE WILL ASSURE YOU UNSURPASSED QUALITY, DESIGN INNOVATION AND COMMITMENT TO CUSTOMER SATISFACTION.

CSDV40D direct vent cast stove with double doors in Graphite

LEXFIRE BURN SYSTEM[™]



Exclusive LexFire Burn System – combines all of the elements of a natural wood fire to produce flames so realistic, you'll forget it's not real wood.

Realistic Logs – starting with hand carved samples that are perfectly proportioned to fit the stove size and viewing area and then color enhanced to match real wood.

Yellow Flames – bright yellow flames appear almost translucent in color.

Log glow – as log surfaces heat up they produce a bright reddish orange glow, similar to wood in the secondary stages of combustion.

Ember Bed – a large area of burning ember replicates the look of wood in the final stages of combustion.

Primary Combustion Zone – primary combustion of fuel load.

LexFire Burn – gas and oxygen are precisely metered and strategically distributed to provide optimum flame presentation.

CAST STOVE FEATURES

- High quality castings
- Large viewing area
 - -126 square inches (CSDV20)
 - -230 square inches (CSDV30)
 - -300 square inches (CSDV40)
- Available in natural or propane gas models
- Robust lively flames, glowing logs and a large ember bed on a pan syle burner provide both ambiance and warmth to any setting
- Reliable millivolt system operates even during power outages
- Operator friendly deluxe control panel with color illustrated decal
- Battery operated pilot ignition system makes startup a snap

• Variable flame control

CSDV20-12,500 to 18,000 Btu/hr input (natural gas) and 15,000 to 19,000 Btu/hr input (propane gas)

CSDV30–17,000 to 28,500 Btu/hr input (natural gas) and 21,000 to 28,000 Btu/hr input (propane gas)

CSDV40–26,000 to 38,000 Btu/hr input (natural gas) and 30,000 to 36,000 Btu/hr input (propane gas)

- Options include a heat activated variable speed blower (excluding CSDV20), remote controls or wall thermostat
- Thermal efficiency up to 80%

OPTIONAL ACCESSORIES

The Concorde Series has many options and accessories available to compliment any style home. Choose from our selection of colors with a choice of graphite, enamel black, brown or sand finishes. Remote controls, wall switch or wall thermostat also available for the added value of convenience.



Multi-functional Ambient Technologies® remote controls available for all units



Programmable wireless wall thermostat with receiver



Warming shelf available in Graphite, Enamel Black, Brown and Sand

Easy snap on fixed bubble screen with decorative handle available in three sizes (For use with double door models only)



with receiver



Touch Light[™] table top/wall mount TLM on/off and TLT thermostat remote control



Enamel Brown



Graphite Enamel Black

Enamel Sand

See our Ambient Technologies® catalog for a complete line of remotes and thermostats.

Specifications

Model	CSDV20	CSDV30	CSDV40	
Shipping Weight (Lbs)	175	200	235	
Width	21.25"	26.25"	29.25"	
Depth 19"	21.75″	23″		
Height 23"	28.5″	30″		
Fire Viewing Area (Sq. Inch)	126	230	300	
Flue Size	4" x 6.625"	4″ x 6.625″	4" x 6.625	
BTU/hr Input Rate (NG)	12,500 - 18,000	17,000 – 28,500	26,000 - 38,000	
BTU/hr Input Rate (LP)	15,000 - 19,000	21,000 - 28,000	30,000 - 36,000	
FE/P4 Ratings (Cdn. Fireplace Efficiency)	51.8% NG / 54.7% LP	53.1% NG / 56.4% LP	57.5% NG / 59.9% LP	
Thermal Efficiency (%)	80	80	80	
Heating Capacity (Sq. ft.)	500	1,200	1,800	

Note: Square foot heating capacities are approximations only. They will vary depending upon the level of insulation, climate, house design, ceiling height, ambient outside temperatures and how the appliance is operated. Tested to Canadian Standards Association's CSAP.4.1-02 testing method for measuring fireplace efficiency.



To avoid personal injury or property damage, the product described by this brochure must be installed, operated and maintained in strict compliance with the instructions packaged with the product and all applicable building or fire codes. Contact local building or fire officials about restrictions and installation inspection requirements. All photographs and drawings on this brochure are for illustrative purposes only and are not intended for, nor should they be used as a substitute for the instructions packaged with the unit. Appearance and specifications of the product are subject to change without notice. © 2009 Monessen Hearth Systems Co.