



Rinnai®

R70e

TANKLESS WATER HEATERS MODEL R70e (2526W)

FOR RESIDENTIAL APPLICATIONS

THE ALL NEW MID-SIZE WATER HEATER

The R70e, which has a maximum capacity of 7.0 GPM, is the new addition to Rinnai's full line of external units, offering a capacity between the R53e and the R85e. The R70e is perfect for 2-3 bathroom homes where space-saving exterior mounting is desired. It's a cost effective way to "right-size" if you don't need the output of the R85e (2532W), and it has a more robust capability than competing models.



ENHANCED FEATURES — ENHANCED PERFORMANCE

The new mid-size unit is a perfect fit for medium-sized residential homes.

MODEL	Degree Rise	GPM	Degree Rise	GPM	Degree Rise	GPM
R85e (2532W)	35° F	8.5	45° F	7.4	55° F	6.1
R70e (2526W)	35° F	7.0	45° F	7.0	55° F	6.1
R53e (2020W)	35° F	5.3	45° F	5.3	55° F	4.6
R42e (1616W)	35° F	4.2	45° F	4.2	55° F	3.6

- Hot water capacity of 0.6 - to 7.0 GPM (at a 35° F rise); 15,000 - 199,000 BTU's
- Packaged with a Rinnai MC-91 controller
- External installation only
- RapidStart® - hot water out in 40% less time and reduces "wasted" water by 26%

NEVER RUN OUT OF HOT WATER

- Endless hot water
- Heats water at a consistent temperature
- Delivers hot water to multiple water sources simultaneously at a constant user-set temperature

SAVE MONEY ON ENERGY COSTS

- Water is heated only as needed when hot water demand is detected




THE RINNAI ADVANTAGE GUARANTEE

- No tank - eliminates standby loss
- Exceptional Warranty - 10 years limited on heat exchanger, 5 years on all other parts, 1 year for labor
- Scald-resistant with use of digital temperature control

OPTIMIZE VALUABLE SPACE

- Frees up valuable internal space
- Can be strategically flush-mounted on an exterior wall without the need for additional venting

EXTERIOR WALL
Exterior installations require no additional venting accessories.



Available Rinnai Recess Box

THE R70e INCLUDES THE FOLLOWING



MC-91 CONTROLLER
Digital control pad to operate at exact user-specified temperatures.

MODEL R70e



MODEL	R70e
Dimensions (Water Heater Unit)	8 ¹³ / ₁₆ " D x 13 ²⁵ / ₃₂ " W x 23 ⁵ / ₈ " H
Weight	46 lbs.
Maximum/Minimum Gas Rate (Input BTU's)	199,000 BTU / 15,000 BTU
Energy Factor	Natural Gas: 0.81 Propane: 0.80
Thermal Efficiency	Up to 84%
Hot Water Capacity Range	0.6 to 7.0 GPM
Maximum Hot Water Capacity (35°F Rise)	7.0 GPM (420 GPH)
Setpoint Temperature (Without Remote)	Factory Setting - 120°F
Temperature Range with Remote Key Pad(s) Connected	MC-91-1: 98° - 140° F

Rinnai is continually updating and improving products; therefore, specifications are subject to change without prior notice. Local, state, provincial and federal codes must be adhered to prior to installation.

CONTACT YOUR LOCAL AUTHORIZED DEALER

Rinnai Corporation

103 International Drive
Peachtree City, GA 30269

Toll Free 1-800-621-9419

Phone: 678-829-1700

Fax: 678-364-8643

Visit Our Web sites www.rinnai.us • www.foreverhotwater.com

E-mail: marketing@rinnai.us

Rinnai®

