

The Vista Insert, the perfect solution for truly efficient, easy wood heat in smaller masonry or factory-built fireplaces. Pacific Energy's user-friendly design means controllable heat and a great view of your wood fire. Standard variable speed fan, clean glass "air wash system", floating firebox and heavy construction mean years of heating comfort.

STA	NDARD FEATURES OPTIONS CHOICES		
	Reliable, durable non-catalytic technology		
	User friendly, one-touch operation		
	Air wash system for super clean ceramic glass		
	High-tech multi-port combustion air injection system		
	Inside and outside combustion air capable		
	Floating firebox for extended stove life		
	Rich Metallic Black finish with black trim		
	Heavy plate-steel top		
	Steel baffle and 304 Stainless Steel insulation cover		
	Boost air for easy lighting		
	80 cfm temperature actuated variable speed blower		
	Screen doors		
	Mantel shield		
	Arched Door available in four finishes		
	Embossed surround, standard size		
	Flat surround, oversize		
	Surround trim available in 3 finishes (Gold, Nickel, Metallic Black)		

AT PUT	Cord Wood	56,000 BTU	
HEAT	EPA Test Fuel	26,300 BTU	
Efficie	ncy (LHV)	80.7%	
Emiss	ions	2.9 gm/hr.	
Log S	ize	18 inches Max.	
36 1/2"	9 3/4" 42 1/2" (Oversize surround) 2 8 8 8 8 8 9 14 1/2" -14 1/2" -1	+14 1/2" + 28 1/4"   Oversize   Surround)   Oversize   Oversize   Surround)   Oversize   Over	