



MEDIUM
For heating up to 2000 sq ft. *

The Super Insert

STANDARD FEATURES ■ OPTIONS ■ CHOICES ■

HEAT OUTPUT	Cord Wood	72,000 BTU
	EPA Test Fuel	34,600 BTU
Efficiency (LHV)		82.6%
Emissions		3.4 gm/hr.
Log Size		18 inches Max.

Wt. 342 lbs

- Reliable, durable non-catalytic technology
- User friendly, one-touch operation
- Air wash system for super clean ceramic glass
- High-tech multi-port combustion air injection system
- Inside and outside combustion air capable
- Floating firebox for extended stove life
- Easy and safe front to back fuel loading
- Rich Metallic Black finish with black trim
- Heavy plate-steel top
- 304 Stainless Steel baffle, insulation cover, rails and flame shield
- Boost air for easy lighting
- 160 cfm temperature actuated variable speed blower/s
- Screen doors
- Mantel shield
- Arched Door available in four finishes
- Radiant Door available in four finishes
- Embossed surround, standard size
- Flat surround, oversize
- Surround trim available in 3 finishes (Gold, Nickel, Metallic Black)

Pacific Energy's best selling wood insert lets you enjoy efficient heating without losing the ambience of an open fire. The Super Insert, with its large, ceramic glass door gives you the full comfort and view of your log fire. Transform your drafty fireplace in an easy-to-light, easy-to-load reliable source of heat.

See page 7 for choices & finishes

PACIFIC ENERGY WOOD STOVES and INSERTS

* Heating capacity will vary depending on type of wood, floor plan, house layout, heat loss of home, and geographical location.