SELECT®

Residential Electric Water Heaters





Tall, Short and Lowboy models available.

Diffuser Dip Tube - Helps reduce lime and sediment buildup, maximizes hot water output. Made of State PEXANTM, a cross-linked PEX polymer that can withstand long-term exposure to water temperatures up to 400°F.

Aluminum Anode Rod - Helps protect against corrosion for longer life.

Durable Tamper-Resistant Brass Drain Valve

Glass-Lined Tank - For long-lasting protection against rust and corrosion.

Upgrade Tank Warranty to 10 Years - See details on page 2.

CSA Certified and ASME Rated T&P Relief Valve - Top-mounted T&P Relief Valve available as option on some models.

Compliance - Meets or Exceeds the Federal Minimum Energy Standards according to the latest edition of the National Appliance Energy Conservation Act (NAECA). Meets the standby loss requirements of the U.S. Department of Energy and current edition of ASHRAE/IESNA 90.1 and ICC and HUD Standards.

6-Year Limited Tank and Parts Warranty Code



For more information on Select® contact: State Water Heaters 500 Tennessee Waltz Parkway, Ashland City, TN 37015 800-365-0024 Toll-free USA www.statewaterheaters.com

SOLID. STATE



SELECT®

Residential Electric Water Heaters



MODEL NUMBER	PEAK DEMAND OUTPUT (1st Hour Rating Gallons)	ENERGY FACTOR	GALLON CAPACITY	ELEMENT WATTAGE 240 VAC				DIMENSIONS IN INCHES			APPROX.
				STANDARD	MAXIMUM	RECOVERY 90°F RISE	R VALUE	A HEIGHT	B DIAMETER	С	SHIPPING WEIGHT (LBS)
TALL MODELS											
ES6 30 DORT	43	.93	30	4500	6000	21	16	46-1/2	18	39-1/2	95
ES6 40 DORT	52	.92	40	4500	6000	21	16	59-1/2	18	53-1/2	115
ES6 52 DORT	60	.91	50	4500	6000	21	16	54	20-1/2	47-1/2	125
ES6 55 DORT	67	.90	55	4500	6000	21	16	60-1/4	20-1/2	52-3/4	135
ES6 66 DORT	72	.88	66	4500	6000	21	16	60-1/4	22	53	170
ES6 80 DORT	81	.86	80	4500	6000	21	16	60-1/2	24	52	200
ES6 80 DORTN	85	.86	80	4500	6000	21	9.2	60	22-5/8	52-1/8	180
ES6 120 DORT *	112	.81	119	4500	6000	21	16	64-1/4	28	54-1/4	320
SHORT MODELS											
ES6 30 DORS	43	.93	30	4500	6000	21	16	36-1/2	20-1/2	28	100
ES6 40 DORS	52	.92	40	4500	6000	21	16	44	20-1/2	37-3/4	115
ES6 50 DORS	62	.90	50	4500	6000	21	16	48	22	40-1/2	150
LOWBOY MODEL				'	•	'	'	'	'	'	
ES6 30 DOLS	41	.93	29	4500	6000	21	16	30	22	22-1/2	105
ES6 40 DOLNS	48	.92	38	4500	6000	21	12	31-1/4	23	24-5/8	120
ES6 50 DOLS	55	.91	50	4500	6000	21	16	34	26-1/2	25	170

Recoveries are rounded to nearest gallon


Water Connections - 3/4" on all models

For 10-Year Tank Warranty, change "6" to "X" in Model Number (ES \underline{X} 40 DORT)

10-Year Tank Warranty and top T&P Valve option combo not available on ES6 40 DOLNS and ES6 50 DOLS

For complete information on limited warranties, consult written warranty, or contact the State Customer Care Center, 1800-365-0024.

State Industries, Inc. reserves the right to make product changes or improvements without prior notice.



*Location for optional top-mounted T&P Valve, if available and ordered from factory.

For more information on Select® contact: State Water Heaters 500 Tennessee Waltz Parkway, Ashland City, TN 37015 800-365-0024 Toll-free USA www.statewaterheaters.com

SOLID STATE



^{*}This model is not available with top-mounted T&P Valve