



neo

Innovative ductless mini split solutions
Wall Mount Heat Pump

Up to 22 SEER



Designed for Single Zone applications like:

Bedrooms | Living Rooms | Dining Rooms | Home Offices | Sunrooms | Basements | Computer / Server Rooms

www.greecomfort.com

neo

Key Features

- High Efficiency G10 Inverter Technology (up to 22 SEER)
- Gold Fin Condenser
- Healthy filter options
- Low Ambient Cooling to 5°F (208-230 Volt systems)
- Low voltage start-up
- Intelligent Defrost
- Intelligent Pre-heating
- Comfortable Sleep Mode
- Auto Swing (Vertical)
- Multiple Fan Speeds
- Auto Clean
- Dry Anti-mildew design
- LED display
- Automatic Operation
- Self-diagnosis
- Memory Function
- Timer
- Control lock
- Fan Delay function



Model	* GWH09MA-A3DNA3A	* GWH12MB-A3DNA3A	* GWH12MB-D3DNA3D	* GWH18MC-D3DNA3D	* GWH24MD-D3DNA3D	GWH30LB-D3DNA3E	GWH36LB-D3DNA3E	
System Type	Heat Pump							
Power Supply	115V / 60Hz	115V / 60Hz	208-230V / 60Hz	208-230V / 60Hz	208-230V / 60Hz	208-230V / 60Hz	208-230V / 60Hz	
Rated Current Cooling	Amps 7.0	11.0	4.5	6.7	7.9	12.1	15.9	
Rated Current Heating	Amps 7.5	12.5	5.2	7.3	9.3	12.5	15.5	
System Performance								
Cooling Capacity (Min-Max)	Btu/h 9,000 (4,435-12,000)	12,000 (4,500-14,000)	12,000 (3,100-13,500)	18,000 (5,970-22,350)	21,400 (9,600-25,000)	28,000 (9,500-30,000)	33,600 (7,400-36,000)	
Heating Capacity (Min-Max)	Btu/h 9,500 (3,200-12,500)	13,000 (3,250-14,500)	13,000 (2,400-14,000)	19,800 (4,100-22,000)	23,000 (4,300-26,000)	28,400 (10,000-33,000)	34,600 (15,000-36,000)	
SEER/EER	22 / 14.2	20 / 12.0	20 / 12.0	18 / 12.0	18 / 12.0	16 / 10.1	16 / 9.2	
HSPF/COP	9.8/4.1	9.6/3.2	9.2/3.2	10.0/3.5	10.0/3.2	8.2/2.9	8.2/2.9	
Indoor Unit								
Air Flow T/H/M/L	CFM 329/294/253/217	300/276/253/217	335/277/253/218	500/459/383/324	588/471/412/353	706/677/647	824/706/677	
Sound Pressure Level T/H/M/L	db (A) 38/34/30/26	40/36/32/26	44/39/36/33	49/44/40/35	53/45/41/37	57/54/48	59/56/53	
Unit Size(WxHxD)	Inches 33.3 x 10.8 x 7.1	33.3 x 10.8 x 7.1	33.3 x 10.8 x 7.1	37.0 x 11.7 x 7.9	39.7 x 12.4 x 8.6	53.1 x 12.8 x 10.0	53.1 x 12.8 x 10.0	
Package Size(WxHxD)	Inches 36.1 x 14.6 x 10.2	36.1 x 14.6 x 10.2	36.1 x 14.6 x 10.2	39.8 x 15 x 11.2	42.4 x 15.7 x 12.9	56.7 x 16.6 x 14.1	56.7 x 16.6 x 14.1	
Net/ Gross Weight	lbs 24 / 31	24 / 31	22 / 29	29 / 38	35 / 46	44 / 60	44 / 60	
Outdoor Unit								
Compressor Type	DC Inverter-Driven Twin Rotary							
Sound Pressure Level	db(A) 53	55	52	56	58	62	65	
Unit Size (WxHxD)	Inches 33.4 x 21.3 x 12.6	33.4 x 21.3 x 12.6	33.4 x 23.2 x 12.6	37.6 x 27.6 x 15.6	38.6 x 31.1 x 16.8	38.6 x 31.1 x 16.8	38.6 x 31.1 x 16.8	
Package Size (WxHxD)	Inches 34.7 x 23.4 x 14.3	34.7 x 23.4 x 14.3	34.7 x 25.4 x 14.3	40.5 x 29.0 x 18.5	42.6 x 33.7 x 19.2	42.6 x 33.7 x 19.2	42.6 x 33.7 x 19.2	
Net / Gross Weight	lb 79 / 90	88 / 97	88 / 97	99 / 110	132 / 146	154 / 163	161 / 170	
Refrigerant / Charge	oz. R410A / 42.9	R410A / 46.4	R410A / 45.9	R410A / 49.4	R410A / 56.5	R410A / 84.7	R410A / 84.7	
Installation								
Line Set Size, Liquid - Suction	Inches 1/4" - 3/8"	1/4" - 3/8"	1/4" - 3/8"	1/4" - 1/2"	1/4" - 5/8"	1/4" - 5/8"	1/4" - 5/8"	
Pre-Charge	Feet 25	25	25	25	25	25	25	
Max.Line Run	Feet 50	50	66	82	82	100	100	
Max.Elevation	Feet 33	33	33	33	33	33	33	
MCA	Amps 22	23	10	13	16	20	24	
MOCP	Amps 35	35	15	20	25	30	35	
Wire Size / # Wires	AWG14 / 4							

* Energy Star Qualified Model



On Select Models



Preserving resources remains our top priority, so we've printed this piece on recycled materials.

GREE

For more information, visit | greecomfort.com



Test conditions are based on AHRI 210/240. Specifications are subject to change without notice. Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice or without incurring obligations. ©2013. All rights reserved. WAT120402-v3