

# Panasonic

## ideas for life



### Multi Zone Submittal Data

Indoor: **CS-E9NKUAW**  
 Wall Mounted Heat Pump

Job Name: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Engineer: \_\_\_\_\_  
 Submitted to: \_\_\_\_\_  
 Submitted by: \_\_\_\_\_  
 Reference: \_\_\_\_\_

Approval: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Construction: \_\_\_\_\_  
 Unit #: \_\_\_\_\_  
 Drawing #: \_\_\_\_\_

<b>Power</b>	<b>V/PH/Hz</b>	<b>230/208/1/60</b>
Circuit Ampacity	(A)	15
Fuse Size, Max.	(A)	15

<b>Indoor Unit</b>		
Fan type		Cross Flow
No. Speeds		5
RPM	(High)	1300
Motor Output	(W)	40
CFM	(QLo/Lo/Me/Hi/SHi)	191/230/311/395/434
Indoor Sound Rating	(Hi) (dB-A)	40
Coil Type		Aluminum Fin & Copper Tube
Fin Type - Pipe Type		Slit Plate - Inner Rifled
Rows - F.P.I		2-19
Face Area	(sq.ft)	2
Drain Connection Size	(in.)	5/8"

<b>Features</b>		
Wireless Remote Controller		Standard
Wired Remote Controller ( CZ-RD516C )		Optional
Controls		Microprocessor
Remote Controller		LCD Wireless Type, Temp, Sensor Built In
Temperature Control		IC Thermostat
Air Louver	(Horizontal)	Manual
	(Vertical)	Automatic
Power Failure Automatic Restart		Built-In
Self-Diagnosis		Built-In
Air Filter		Washable, Anti-Mold

<b>Refrigerant</b>		<b>R410A</b>
Control		Electric Expansion Valve
Connection		Flare
Line Size	(in. O.D. Discharge)	1/4"
Line Size	(in. O.D. Suction)	3/8"

<b>Dimensions</b>	(in.)	Height	Width	Depth
Indoor Unit	(Uncrated)	11-7/16"	34-9/32"	8-1/16"
<b>Weight</b>				Indoor
Net	(lbs.)			20
Shipping	(lbs.)			

Performance Data @ ARI Standard Conditions (230/208V)

<b>Cooling</b>		
Total Capacity	(BTU/H)	10200
SEER		21
Dehumidification	(Pints/H)	1.3

<b>Heating</b>		
Total Capacity	(BTU/H)	14100
HSPF		10.5

<b>Operating Range</b>		
Cooling	Maximum	Indoor Air Intake Temp. 90F DB/74F WB
	Minimum	60F DB/52F WB
Heating	Maximum	86F DB/-F WB
	Minimum	60F DB/-F WB

# Indoor Dimensions

