

 \triangleleft

_

ш

CAP



DIRECT VENT GAS FIREPLACE INSERT



EVOLUTIONARY STYLE. REVOLUTIONARY FLEXIBILITY.

MINIMUM FIREPLACE OPENING			
	WIDTH	HEIGHT	DEPTH
IDV33	26 ¹ /4"	21 3⁄8"	I4 ¾"
IDV36	30 ³ /4"	25 ⁵∕ ≋"	I4 ³⁄8"

MINIMUM UNIT COVERAGE

IDV33	WIDTH	HEIGHT	IDV36	WIDTH	HEIGHT
IDV33 (Louvers) IDV33 (Clean View*)	34 ¹ /2" 32 ³ /4"	24 ³ /8" 22 ³ /4"	IDV36 (Louvers) IDV36 (Clean View*)	39" 37 ¼"	28 ³⁄4" 27"
*Back Frame Dimension of Clean View Kit					

LOUVER KIT AND SURROUND SIZES

IDV33	WIDTH	HEIGHT	IDV36	WIDTH	HEIGHT
I33LK (Louver Kit) I33S3426B (Surround) I33S4028B (Surround) I33S4430B (Surround) I33S4535B (Surround)	34 ¹ /2" 34 ¹ /2" 40" 44" 45"	24 ³ /8" 26 ¹ /2" 28 ¹ /4" 30 ⁵ /8" 35"	136LK (Louver Kit) 136S3931B 136S4432B 136S4736B	39" 39" 44" 47"	28 ³ /4" 31 ³ /4" 32 ³ /8" 36"

CLEAN VIEW AND SURROUND SIZES

IDV33	WIDTH	HEIGHT	IDV36	WIDTH	HEIGHT
I33CV (Clean View) I33SPFI I33SSI	35 %" 39 %" 39 %"	24 ¼" 29 ‰" 26"	I36CV (Clean View) I36SSI	40" 43 ½"	28 ½" 30 ¼"



Unit illustrated is a IDV33LP Direct Vent Fireplace Insert – Propane, LOGF35 Split Fiber Oak Log Set, I33CVCV Clean View Kit – Copper Vein, I33SSICV Surround for Clean View – Copper Vein, IDV33RL Refractory Brick Liner.



Unit illustrated is a IDV33LP Direct Vent Fireplace Insert – Propane, LOGF35 Split Fiber Oak Log Set, 133CVPW Clean View Kit – Pewter, 133SSIPW Surround for Clean View – Pewter, IDV33RL Refractory Brick Liner.

Model	IDV33N	IDV33LP	IDV36N	IDV36LP
Fuel	natural	propane	natural	propane
Input	31,000 BTU	28,500 BTU	34,250 BTU	30,000 BTU
Low	20,900 BTU	23,100 BTU	24,000 BTU	22,840 BTU
Output	23,250 BTU	21,375 BTU	25,688 BTU	22,500 BTU
Efficiency	75%	75%	75%	75%
FE (P.4.1-02)	57.4%	57.9%	58.4%	59.9%

STANDARD FEATURES*

- > Dual Burner with glowing embers
- > Millivolt valve system allows operation during power failure with Hi-Low heat and flame adjustment
- > Matchless Piezo Ignition
- > Decorative Ash Bed
- > Log Set Fibre Split Oak or Contemporary Rock Collection.*
- > Ceramic Glass
- > On/Off Rocker switch
- > Heat activated blower with variable speed control
- > Mobile home, bedroom and bed sitting room approval

OPTIONAL FEATURES

Clean View Kit – Black, Pewter or Copper Vein

Surrounds for Clean View – Black, Copper Vein and Pewter

Surround Picture Frame for Clean View – Black

Louver Kit for Grills – Grills available in Black, Classic Series Black with Antique, Chrome, or Polished Brass accents

Surrounds for Louver Kit – Black

Wall Mount Thermostat – Standard On/Off or Programmable 5 day (weekday) and 2 day (weekend)

Remote Control – On/Off or Thermostat, or Modulating Thermostat.

Overlay Black Arch Door – Deluxe, Top Half, Double Arch and Double Door Designer Doors – Arch or Straight with optional Antique, Chrome, or Polished Brass trims.







2340 Logan Avenue Winnipeg, Manitoba, Canada R2R 2V3 Phone: 204.632.1962 Fax: 204.632.1960 www.marguisfireplaces.net Kingsman Fireplaces, maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation. Certification: The models IDV33 and IDV36 are certified for Canada/IUSA as a Vented Gas Fireplace Heater ANSI 221.88-2009, (SSA 2.33-2009, (SGA 2.31-CM)).

*Components may have to be ordered separately to create a complete unit Discuss with your local Kingsman dealer for clarification