

ZERO CLEARANCE DIRECT VENT GAS FIREPLACE




EVOLUTIONARY STYLE. REVOLUTIONARY FLEXIBILITY.



Model	MQHBZDV3636N MQHBZDV4236N	MQHBZDV3636LP MQHBZDV4236LP	MQHBZDV4736N	MQHBZDV4736LP	HBZDV3624N HBZDV4224N	HBZDV3628N HBZDV4228N	HBZDV3624LP HBZDV4224LP	HBZDV3628LP HBZDV4228LP
Flue	top	top	top	top	top	top	top	top
Fuel	natural	propane	natural	propane	natural	natural	propane	propane
Input Max.	30,500 BTU	29,000 BTU	40,000 BTU	36,000 BTU	24,000 BTU	28,000 BTU	22,000 BTU	26,000 BTU
Input Min.	20,600 BTU	22,200 BTU	27,000 BTU	30,000 BTU	14,000 BTU	20,000 BTU	15,000 BTU	19,000 BTU
Output Max.	22,875 BTU	21,750 BTU	-	-	-	21,000 BTU	15,000 BTU	19,500 BTU
Efficiency	75%	75%	_	_	_	76% fan on	_	<b>76</b> % fan on
<b>FE</b> (P.4.1-02)	60.9%/56.8%	62.4%/56.8%	46.5%	42.5%	51.0%/44.7%	58.7%/57.7%	46.0%/47.9%	62.4%/58.6%

## Corner Framing Dimensions (inches)

LOUVERED				CLEAN VIEW CIRCULATING KIT (CVCK)			
	HB36	HB42	HB47		HB36	HB42	HB47
Α	5413/16"	5813/16"	651/4"	Α	59 <sup>7</sup> /8"	6313/16"	703/16"
В	363/8"	423/8"	473/8"	В	38 <sup>7</sup> /16"	427/16"	483/8"
С	36"	41 <sup>7</sup> /8"	471/16"	С	381/6"	421/16"	481/16"
D	93/16"	81/4"	815/16"	D	1011/16"	1011/16"	107/8"
Е	383/4"	415/8"	461/8"	E	425/16"	451/8"	495/8"
F	123/8"	133/4"	1315/16"	F	123/8"	133/4"	1315/16"
G	179/16"	191/2"	1911/16"	G	179/16"	191/2"	1911/16"
Н	273/8"	297/16"	325/8"	Н	2915/16"	31 <sup>7</sup> /8"	351/16"



Top Flue Model	Width	Height				
VIEWING AREA						
HB36	293/4"	185/8"				
HB42	333/8"	203/8"				
HB47	391/2"	26 <sup>3</sup> /8"				

Top Flue Model	Height		Front Width		Depth			
Top Flue Model	Actual	Framing	Actual	Framing	Actual	Framing		
LOUVERS								
HB36	3413/16"	35"	36"	363/8"	167/16"	17"		
HB42	37"	371/8"	41 <sup>7</sup> /8"	423/8"	167/16"	17"		
HB47	431/16"	431/8"	471/16"	473/8"	197/16"	191/2"		
CLEAN VIEW CIRCULATING KIT (CVCK)								
HB36	3411/16"	41"	381/16"	38 <sup>7</sup> /16"	18 <sup>7</sup> /8"	<b>19</b> <sup>1</sup> /2"		
HB42	3613/16"	43"	42 1/16"	427/16"	1815/16"	191/2"		
HB47	49"	491/8"	481/16"	483/8"	2115/16"	22"		

## STANDARD FEATURES

- > Millivolt valve system allows operation during a power failure with Hi/low heat and flame adjustment
- > Dual burner with Realistic Flame Pattern
- > A flame sensor that constantly monitors the pilot flame and provides 100% gas shut off if pilot is not sensed

## **OPTIONAL FEATURES**

Designer Clean View Circulating Kit – No Louvers Required, Optional Pull Screens

Decorative Black Panels or Grills - Grills available in Black.

Classic Series Black with Polished Brass, Antique or Chrome Accents

Overlay Doors - Deluxe, Top Half, Double Arch and Double Door

Designer Doors – Arch or Straight Black Doors with Antique, Polished or Chrome Trims

Surrounds Wide (Louvered Units) - Polished Brass, Antique or Chrome

Surrounds Slim Line (Louvered Units) - Polished Brass,

Antique Brass, Chrome or Gun Metal Black,

Fan Kit - Heat activated with variable speed control

Brick Refractory Liner - Traditional, Herringbone or Classic (36" model only)

Thermostat - Wall Mount Millivolt Thermostat or Programmable Thermostat

Remote Control - On/Off, Thermostat On/Off, Hi/Lo On/Off

Child Safety Screen

Porcelain Reflective Liner

Log Set or Contemporary Rock Collection

Wall Surrounds - Convex, Concave with Black or Pewter finishes









2340 Logan Avenue Winnipeg, Manitoba, Canada R2R 2V3 Phone: 204.632.1962 Fax: 204.632.1960 www.marquisfireplaces.net Kingsman Fireplaces maintains a program of continuous testing refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation.

Certification: The models MQHBZDV4736 and HBZDV3624/4224 are certified to ANSI Z21.50a-2008/CSA 2.22a-2008, CGA 2.17-M91 vented gas fireplace. The models MQHBZDV3636/4236 and HBZDV3628/4228 are certified to ANSI Z21.88b-2008, CSA 2.33b-2008, CGA 2.17-M91 vented gas fireplace heater.

B057 - 09/09