

Submittal Data: System 18RCLX AUU18RCLX & AOU18RLX



Job Name: _____ Location: _____

Purchaser: _____

Engineer: _____

Submitted To: _____ For: Reference Approval Construction

Submitted By: _____

Unit Designation: _____ Schedule No. _____ Model No.: _____

Capacities:

Cooling	17,800/21,500 BTU/h
Outdoor Design Temperature <i>F^o DB/WB</i>	95/75
Heating	21,500/25,600 BTU/h
Outdoor Design Temperature <i>F^o DB/WB</i>	47/43
SEER	16.0
EER <i>Clg/Htg</i>	11.1/10.2

Indoor Unit:

Power Supply	230 V
Noise Level Cooling <i>db (A) - H/ M/ L/</i>	42/39/36
Noise Level Heating <i>db (A) - H/ M/ L/</i>	40/38/36
Weight	75 lbs.

Outdoor Unit:

Power Supply	230 V
Recommended Fuse Size	20A
Min. Ampacity	15.4A
Running Current <i>Cooling</i>	7.0/12.5A
Running Current <i>Heating</i>	8.9/12.5A
Weight	141 lbs.

Refrigerant Piping:

Max Ht. Difference	65/20 ft.
Max Total or Combined Length	165 ft. each
Discharge Vapor Line (O.D.)	1/4 in.
Suction (O.D.)	1/2 in.

Standard Features:

- ◆ Six year compressor warranty
- ◆ Two year parts warranty
- ◆ Weekly timer
- ◆ Auto Louver: Up/Down
- ◆ Energy saver
- ◆ Pump Down Operation
- ◆ Slender fit
- ◆ Built in Low Ambient
- ◆ Auto Restart/ Reset
- ◆ Auto Mode
- ◆ High Ceiling Mode
- ◆ Branch Duct Capable
- ◆ Full Function Wired Remote Control
- ◆ Dry mode
- ◆ Refrigerant R410A
- ◆ Quiet Mode
- ◆ Cold Prevention

Notes:

OUTLINE AND DIMENSIONS

