

### **RUUD** SALES FACT SHEET

R95T- SERIES 95% A.F.U.E.† Models with Input Rates of 40 to 115 kBTU [11.72 to 33.71 kW]



#### **GENERAL TERMS OF LIMITED WARRANTY\***

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Heat Exchanger ......Limited Lifetime Conditional Parts

# Ruud *Achiever Plus*™ Series Multi position Gas Furnaces

#### **Features**

- 95% residential gas furnace CSA certified
- 4 way multi-poise design
- PlusOne<sup>™</sup> Diagnostics 7-Segment LED all units
- PlusOne<sup>™</sup> Ignition System DSI for reliability and longevity
- PlusOne<sup>™</sup> Water Management System with patented Blocked Drain Sensor
- Heat exchanger is removable for improved serviceability. Primary is constructed of aluminized steel, secondary is constructed of stainless steel for maximum corrosion resistance and thermal fatigue reliability.
- Low profile "34 inch" cabinet ideal for space constrained installations.
- Blower Shelf design serviceable in all furnace orientations
- Pre marked hoses insures proper system drainage
- Vent with 2" or 3" PVC
- Replaceable Collector box
- Hemmed edges on cabinet and doors
- Constant Torque electrically commutated motor
- Quarter turn fasteners for tool less access
- Integrated control boards feature dip switches for easy system set up
- Self priming condensate trap
- Solid bottom included

MODEL	INPUT- BTU/HR [kW] ①	HEATING CAPACITY BTU/HR [kW]	HEATING CFM @ .2" [.049 kPa] W.C. E.S.P. [L/s]	COOLING CFM @ .5" [.124 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS.) [kg]	PRICE
R95TA040	42,000 [12.31]	40,320 [11.82]	982 [463]	1239 [585]	123.5 [56]	
R95TA060	56,000 [16.41]	53,760 [15.75]	913 [431]	1227 [579]	128 [58]	
R95TA070	70,000 [20.51]	67,200 [19.68]	1113 [525]	1198 [565]	132 [60]	
R95TA085	84,000 [24.62]	80,640 [23.63]	1574 [743]	1833 [865]	147.5 [67]	
R95TA100	98,000 [38.71]	94,080 [37.16]	1651 [779]	1975 [932]	152 [69]	
R95TA115	112,000 [32.82]	107,520 [31.51]	1524 [719]	1748 [825]	165 [75]	

Note: Above data and specs are for upflow models.

#### [ ] Designates Metric Conversions









Department of Energy test procedures.

\*For complete details of the Limited and Conditional Warranties, including applicable terms and conditions, contact your local contractor or the Manufacturer for a copy of the product warranty certificate.



## **SALES FACT SHEET**

R95T ACCESSORIES					
Description	Part No.	Price			
Condensate Pump Kit	1PCB151TUL				
External Bottom Filter (Upflow/Horizontal) Rack	RXGF-CB				
External Side Filter Rack	RXGF-CD				
External Downflow Top Filter Rack	RXGF-CC				
Fossil Fuel Kit	FXPF-F01				
Fossil Fuel Kit	RXPF-F02				
Downflow/Horizontal Conversion Kit	RXGY-CK				
Downflow/Horizontal Left Zero Clearance Conversion Kit	RXGY-ZK				
Combustible Floor Base	RXGC-B17				
Combustible Floor Base	RXGC-B21				
Combustible Floor Base	RXGC-B24				
Direct Vent Furnace Side Wall Vent 2" or 3"	RXGY-G02				
LP Conversion Kit	RXGJ-FP33				
Neutralizer Kit	RXGY-A01				
Return Air Plenum	RXGR-C17B				
Return Air Plenum	RXGR-C21B				
Return Air Plenum	RXGR-B24C				
Vent Termination Kit - Concentric Horizontal/Vertical (US & Canadian Installations) 3" Pipe	RXGY-E03A				
Vent Termination Kit - Concentric Horizontal/Vertical (US & Canadian Installations) 2" Pipe	RXGY-E02A				
Vent Termination Kit - Concentric Horizontal/Vertical (US Installation Only) 2" Pipe	RXGY-E02				
Vent Termination Kit - Concentric Horizontal/Vertical (US Installation Only) 3" Pipe	RXGY-E03				
Indoor Coil Casing	RXBC-D17AI				
Indoor Coil Casing	RXBC-D21AI				
Indoor Coil Casing	RXBC-D24AI				
Indoor Coil Casing	RXBC-D21B1				
Combustion Air Drain Kit 2"	RXGY-D05				
Combustion Air Drain Kit 3"	RXGY-D06				