RUUD SALES FACT SHEET

13PJP- SERIES

Efficiencies up to 13 SEER Nominal Sizes 1.5 to 4 Tons [5.28 to 14.7 kW] Cooling Capacities 17.7 to 48.5 kBTU [5.19 to 14.2 kW]



GENERAL TERMS OF LIMITED WARRANTY

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Value Series Heat Pumps

Features

- Coils constructed with copper tubing and enhanced aluminum fins.
- Includes factory installed low pressure control.
- Strong, attractive cabinet—louvered design protects the coil from damage.
- Piston metering device with suction line accumulator.
- Demand Defrost Control
- Non-Cycling Reversing Valve
- Hot Gas Muffler
- Service Valves
- Grille/motor mount for quiet fan operation.
- Easily accessible control box.
- Bi-Directional Filter Drier (shipped not installed)
- Certified and rated under AHRI Standard 240.
- U.L listed.

MODEL	Nominal Cooling Capacity (BTU/HR)	VOLTAGE	PHASE	HEIGHT	WIDTH	LENGTH	Shipping Weight	Service Valve - Liquid	Service Valve - Suction	PRICE
18	18,000	208/230	1	26 - 1/4"	23 - 5/8"	23 - 5/8"	152	3/8"	3/4"	
24	24,000	208/230	1	26 - 1/4"	23 - 5/8"	23 - 5/8"	138	3/8"	3/4"	
30	30,000	208/230	1	26 - 1/4"	27 - 5/8"	27 - 5/8"	208	3/8"	3/4"	
36	36,000	208/230	1	27 - 3/8"	31 - 5/8"	31 - 5/8"	227	3/8"	7/8"	
42	42,000	208/230	1	35 - 3/8"	31 - 5/8"	31 - 5/8"	214	3/8"	7/8"	
48	48,000	208/230	1	35 - 3/8"	31 - 5/8"	31 - 5/8"	217	3/8"	7/8"	





ENERQUIDE Seasonal Energy Efficiency Ratio (SEER) <u>This Burger</u> 13.0— Uses least energy →21.0







Ruud Heating, Cooling and Water Heating P.O. Box 17010, Fort Smith, AR 72917

RUUD SALES FACT SHEET

ACCESSORIES								
Description	Part No.	Price						
Blower Time Delay Control	RXMD-C04							
High Pressure Control	RXAB-A07							
Low Ambient Control (RXAD-A08)	RXAD-A08							
Compressor Time Delay Control	RXMD-B01							
Heat Pump Thermostat Warning Light Kit	RXPX-D01							
Heat Pump Monitor	RXPM-B01							

