

## **JUD** SALES FACT SHEET



Featuring
Earth-Friendly
R-410A Refrigerant





## 14PJM SERIES

**14 P**14 SEER P = HEAT PUMP

<u>J</u> VOLTAGE M DESIGN SERIES

J = 208-230 SINGLE PHASE

M = 2ND DESIGN (R-410A) RUUD

## **Features**

- Coils constructed with copper tubing and enhanced aluminum fins
- Strong, attractive cabinet—louvered design protects the coil from damage
- Expansion Valves with Internal Check Valve—provides for quieter refrigerant metering
- Enhanced Demand Defrost Control
- Factory installed low pressure control
- Non-Cycling Reversing Valve
- Hot Gas Muffler
- Service Valves
- Grille/motor mount for quiet fan operation
- Easily accessible control box
- Bi-Directional Filter Drier (shipped not installed)
- Certified and rated under ARI Standard 240
- U.L. listed

## **GENERAL TERMS OF LIMITED WARRANTY**

Ruud will furnish a replacement for any part of this product which fails in normal use and service within the applicable periods stated, in accordance with the terms of the limited warranty.

Condenser Coil leaks caused by	
factory defects	Five (5) Years
Conditional Compressor*	Ten (10) Years
Any Other Part	Five (5) Years
*See Product Warranty Card for Details.	

<u>18</u>

01

NOMINAL COOLING CAPACITY

18 = 18,000 BTU/HR [5.28 kW]

24 = 24,000 BTU/HR [7.03 kW] 30 = 30,000 BTU/HR [8.79 kW] 36 = 36,000 BTU/HR [10.55 kW]

42 = 42,000 BTU/HR [12.31 kW] 48 = 48,000 BTU/HR [14.07 kW] 60 = 60,000 BTU/HR [17.58 kW]  $\frac{\text{CABINET}}{\text{A = FULL METAL JACKET}}$ 

Α

RUUD VALUE SERIES

Price Starting at:









