# Accessories

Manifold Systems & Vent Kits

designed to customize your Rheem tankless installation



#### TANKLESS ACCESSORIES



#### **Recess Boxes**

Recess boxes enhance an outdoor installation by protecting the tankless unit from damage and tampering. They also provide additional protection from extreme

- RTG20170 for the RTG-66X 36-1/2" high, 14-3/4" wide, 8-1/2" deep
- RTG20038 for the RTG-74X and GT-199X 41" high, 17" wide, 10" deep
- RTG20065 for the RTG-53X 35" high, 14-3/4" wide, 5-5/8" deep



#### **Cosmetic Pipe Covers**

Cosmetic pipe covers enhance an indoor or outdoor installation by concealing the pipe beneath the water heater. They provide protection from tampering and weather conditions.

- RTG20169DVG for the RTG-66DV (grey)
- RTG20169DV for the RTG-66DV (beige)
- RTG20169XG for the RTG-66X (grey)
- RTG20037G for the RTG-74 or GT-199 (grey)
- RTG20037 for the RTG-74 or GT-199 (beige)
- RTG20063DV for the RTG-53DV (beige)
- RTG20063PV for the RTG-53PV or X (beige)



#### Service Valve Kit

Service valves allow for easy installation and maintenance of your tankless water heater. They provide unions for easy removal of the water heater and water hose connections for use with a flush kit. Includes the AP12993C relief value.

• RTG20111-1



#### **Pressure Relief Valve**

The pressure relief valve is a necessary part to every tankless installation. It is designed to relieve any excess build up of pressure on the plumbing system that could damage the water heater or other plumbing equipment.

AP12993C



#### **Remote Controls**

Remote controls allow you to easily adjust the operational temperature of the water heater. You can have up to three, one of each type, on a single tankless water heater, allowing you to set the temperature from just about anywhere in your home.

- RTG20006DW UMC-117 main remote control
- RTG20006DU USC1-117 bath remote control
- RTG20006DV USC2-117 second bath remote control
- RTG20009-1 10 ft. thermostat wire



#### Flush Kit

The Flush kit is designed to work in conjunction with the service valves, when used properly the flush kit can be used to reduce the lime scale buildup that occurs in the tankless water heater. Includes 5-gallon bucket, submersible pump, and two steel hoses.

• RTG20124

#### TANKLESS MANIFOLD SYSTEMS

#### MIC-180 Manifold Controller

• RTG20126A manifold and control up to 6 tankless models.\* Includes installation cabinet for indoor or outdoor applications.

#### MICS-180 Manifold **Controller Expansion Card**

• RTG20126B Add on the MIC-180 for up to 20 units in total.\*\* Installations of 7 to 20 require this expansion card. Mounts inside the MIC-180 cabinet. Includes cables to connect to the MIC-180 board.









#### **Manifold Control Cables**

One required for each tankless water heater installed in a manifold. Connects a single tankless water heater to the MIC-180

- RTG20126C MIC-K-16 16 ft. control cable
- RTG20126D MIC-K-32 32 ft. control cable
- RTG20126E MIC-K-65 65 ft. control cable



#### **EZ-Link Cable**

• RTG20040

Connect two tankless water heaters† together in a manifold\*\*

- Only RTG-53, RTG-74, RTGL-74 with a -1 or greater suffix on the model number, and all GT-199, RTG-66 and RTGL-74 models.
- \*\* This card provides control cable connection points for units 7 20 in multi-unit manifold.
- \*\*\* Only two units may be connected together with the EZ-Link Cable.
- † Only RTG-53 models, or RTG-74 and GT-199 models that have a -1 or greater suffix or RTG-66 and RTGL-74 can be used with the EZ-Link Cable.

#### **TANKLESS DIRECT VENT KITS**



#### 3"/5" Horizontal Concentric Vent Kit

Horizontal termination kit of RTG-66DV and RTG-53DV for up to a 10" wall thickness.

 RTG20147-1 Contains appliance adapter, a 94 degree elbow, long termination, a 12" wall plate, and screws. For up to a 10" wall thickness.



#### 3"/5" Vertical Vent Kit

Vertical termination kit of RTG-66DV and RTG-53DV. Does not contain vertical vent piping.

 RTG20184 Contains vertical appliance adapter with integrated condensate collector, vertical termination cap, 12/12 roof flashing, storm collar, condensate drain line, and screws.

Kit does not include vent pipe, additional pipe must be purchased separately to complete the installation.



#### Horizontal Termination Kit for 74DV

• RTG20197 Kit converts the two-pipe DV unit for use with up to 9 ft. of standard 3"/5" concentric vent. Horizontal kit is for up to 10" wall thickness. Contains two-pipe to concentric box adapter, 94 degree elbow, long termination, a 12" wall plate, and screws.



## Vertical Termination Kit for 74DV

• RTG20207 Kit converts the twopipe DV unit for use with up to 9 ft. of standard 3"/5" concentric vent. Add up to 9 ft. of vertical vent pipe. Contains two-pipe to concentric box adapter, vertical condensate collector, vertical termination cap, 12/12 roof flashing, storm collar, condensate drain line, and screws.

Kit does not include vent pipe, additional pipe, up to 9 ft., must be purchased separately to complete the installation.



#### **Direct Vent Termination Kits**

- RTG20034HPT-1 for 74DV and GT-199DV vent termination (fits Protech or Z-Flex vent). Contains (2) 12" face plates, (1) 12" length of 4"/7" concentric pipe, (1) horizontal termination adapter, (1) air Intake tee, (8) screws.
- RTG20035VPT 74DV and GT-199DV vent termination (vertical for Protech vent). Contains (1) 36" length of 4"/7" concentric pipe, (1) air intake tee, (1) vertical termination adapter, (1) vertical termination outlet with rain cap, (8) screws.
- RTG20191 adapter for Metal Fab to connect to RTG20034HP-1 or RTG20035VPT.
- AP13979 air intake connector, 4" x 4-1/2" rubber coupling for using PVC as an alternate air intake vent with the 74DV and GT-199DV models.

#### TANKLESS SINGLE WALL VENT KITS



#### 4" Horizontal Vent Kit

- RTG20195 for RTG-74PV and TRGL74P. Dampered design for cold climates\* 4"/7" adjustable wall thimble, 0"/3-1/2" adjustable horizontal and vertical run, UL listed to 1738, AL29-4C stainless steel construction.
- RTG20196 3" vent kit available.
- \*Cold climates are those where the average daily temperature drops below freesing for extended periods.



#### 4" Single Wall Vent Kit

 RTG20155 4CGSWPHK includes RTG20146 appliance adapter, RTG20150B 12" vent length, RTG20150J adjustable vent length, (2) RTG20150D 90 degree elbows, RTG20150W 90 degree termination, RTG20250K wall thimble, AP12993C relief valve, RTG200009-1. T-stat wire.



#### 3" Single Wall Vent Kit

• RTG20154 3CGSWPHK includes RTG20145 appliance adapter, RTG20149D 12" vent length, RTG20149F adjustable vent length, RTG20149C 90 degree elbows, RTG20149U 90 degree termination, RTG20149B wall thimble, AP12993C relief valve, RTG200009-1. T-stat wire. More Rheem water heaters have been installed in homes than any other brand. Rheem has been providing reliable water heating to the world since we invented the water heater over 100 years ago.

### Premier Customer Experience Priority One!

Rheem Water Heating will be the premier customer experience provider of Rheem tankless water heaters. Rheem's philosophy of speed, accuracy and attentiveness will guide this initiative. This will be achieved through customer education, internal and external training, and after sales service.



For more information, call 1-866-720-2076 or visit rheemtankless.com

In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.



# Tankless water heaters Endless hot water

Rheem Water Heating and Heating & Cooling Products 101 Bell Road, Montgomery, AL 36117-4305 1-866-720-2076 • www.rheem.com

Rheem Canada Ltd./Ltée • Water Heater Division 125 Edgeware Road, Brampton, Ontario L6Y 0P5

Rheem manufactures residential and commercial heating & cooling and water heating products.

Printed in U.S.A. 07/09 WP 101-70 Rev. 6



