



SALES FACT SHEET



Featuring
New Industry Standard
R-410A Refrigerant

R-410A



14PJM SERIES

Features

- Coils constructed with copper tubing and enhanced aluminum fins
- Strong, attractive cabinet—louvered design protects the coil from damage
- Expansion Valves with Internal Check Valve—provides for quieter refrigerant metering
- Enhanced Demand Defrost Control
- Factory installed low pressure control
- Non-Cycling Reversing Valve
- Hot Gas Muffler
- Service Valves
- Grille/motor mount for quiet fan operation
- Easily accessible control box
- Bi-Directional Filter Drier (shipped – not installed)
- Certified and rated under ARI Standard 240
- U.L. listed

GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable periods stated, in accordance with the terms of the limited warranty.

Conditional Parts Warranty* (Registration Required)	Ten (10) Years
Conditional Compressor* (Registration Required)	Ten (10) Years
Limited Parts	Five (5) Years

*See Product Warranty Card for Details.

14	P	J	M	18	A	01
14 SEER	P = HEAT PUMP	VOLTAGE J = 208-230 SINGLE PHASE	DESIGN SERIES M = 2ND DESIGN (R-410A)	NOMINAL COOLING CAPACITY 18 = 18,000 BTU/HR [5.28 kW] 24 = 24,000 BTU/HR [7.03 kW] 30 = 30,000 BTU/HR [8.79 kW] 36 = 36,000 BTU/HR [10.55 kW] 42 = 42,000 BTU/HR [12.31 kW] 48 = 48,000 BTU/HR [14.07 kW] 60 = 60,000 BTU/HR [17.58 kW]	CABINET A = FULL METAL JACKET	RHEEM VALUE SERIES

Price	Starting at: \$
-------	--------------------

