



# SALES FACT SHEET



## CLASSIC® SERIES SUPER QUIET 80™ 80% A.F.U.E.† DOWNFLOW GAS FURNACES w/ECM MOTOR

**RGLT- SERIES**  
ECM Equipped  
Models with Input Rates  
from 75,000 to 125,000 BTU/HR  
[22 to 37 kW]

(U.S. & Canadian Models)

### GENERAL TERMS OF LIMITED WARRANTY

Rheem will furnish a replacement for any part of this product which fails in normal use and service within the applicable period stated, in accordance with the terms of the limited warranty.

Gas Heat Exchanger Limited Warranty . . . . .Twenty (20) Years  
Conditional Parts\* (Registration Required) . . . . .Ten (10) Years

\*Refer to Product Warranty Card for details.

### Features

- ECM X-13 Motor for reduced power consumption and improved A/C efficiency.
- Innovative design results in reliable, efficient operation at sound levels which provide distinct competitive advantage.
- Patented heat exchanger, constructed of both stainless and aluminized steel for the maximum in corrosion resistance.
- Low profile "34 inch" [864 mm] design is lighter and easier to handle, and leaves room for optional equipment.
- Left or right side gas and electric inlet connections with quick, simple change.
- Direct Spark ignition.
- Integrated board with humidifier and electronic air cleaner hookups.
- Insulated blower compartment helps to reduce jacket loss and noise.
- Pre-paint galvanized steel cabinet.
- Molded permanent filter.
- Grab-holes in doors to aid in easy door removal and replacement.

A variety of cooling coils and plenums designed to use with Rheem *Classic® Series Super Quiet 80™* gas furnaces are available as optional accessories.

†A.F.U.E. (Annual Fuel Utilization Efficiency) calculated in accordance with Department of Energy test procedures.

MODEL	INPUT- BTU/HR [kW] ②	HEATING CAPACITY BTU/HR [kW] ①	HEATING CFM @ .5" [.049 kPa] W.C. E.S.P. [L/s]	COOLING CFM @ .5" [.12 kPa] W.C. E.S.P. [L/s]	APPROX. SHIPPING WEIGHT (LBS.) [kg]	PRICE
RGLT-07*AMKR	75,000 [22.0]	60,000 [18]	1236 [583]	1200 [566]	105 [47.6]	
RGLT-07*AMGR	75,000 [22.0]	60,000 [18]	1451 [685]	2000 [944]	120 [54.4]	
RGLT-10*BRMR	100,000 [29.3]	81,000 [24]	1766 [833]	2000 [944]	120 [54.4]	
RGLT-12*ARMR	125,000 [36.6]	99,000 [29]	1722 [813]	2000 [944]	140 [63.5]	

① In accordance with D.O.E. test procedures.

② See Conversion Kit Index Form for high altitude derate in U.S. applications. For Canadian applications, reference the furnace installation instructions.

\*E=Standard, N=NO<sub>x</sub> Models

[ ] Designates Metric Conversions

