

[Back to top](#)



Specifications Chart Model: NS3

Capacity/Lifespan:	Lifetime within application guidelines
Service Flow Rate:	Service flow of 8-12 gpm (Note: The average household requires a service flow of approx. 6 gpm)
System Plumbing Size:	All NaturSoft™ Systems are shipped Ready-To-Install including necessary fittings for ¾” and 1” pvc and copper plumbing installations.
Pre-filter:	5-micron pre-filter used to filter out potential cysts, copepods, sediment and /or particulate matter down to 5-micron in size. (Includes housing, pre-filter, bracket, and screws) Dimensions: 7 ¼” x 13”
Water Flow type:	Up flow Design to eliminate channeling- present in most down flow systems, no backwashing needed
Installation Kit:	Provided with the NaturSoft™ System: <ul style="list-style-type: none">• 1 Bypass valve assembly• 1” brass sweat adapter kit• ¾” brass sweat adapter kit• 1” pvc threaded gray 90 degree elbow adapter kit• ¾” x 1” pvc solvent gray 90 degree elbow adapter kit
Operating Pressure Range:	10-125psi
Operating Temperature Range:	Up to 150 Degrees F
pH Range:	7.0 - 11.00 pH
Oil Tolerance:	No Oil
Copper Tolerance:	< 0.30 mg/L
Hardness/Water Softening:	Up to 75 grains per gallon
Surface of Media:	Nano Surface
Hydrogen Sulfide Max:	Pre-Treatment required
Minimum Installation	Tank size is 9” in diameter x 49” in height

[Back to top](#)

[Back to top](#)

Floor Space:	
Total Shipping Weight:	NaturSoft™ complete system with installation kit weighs approx. 35lbs.
Warranty:	Performance Guarantee 10-year parts warranty

[Back to top](#)