

2506 South Elm Street
Greenville, IL 62246
www.enertechgeo.com
info@enertechgeo.com

RT Models Split System Water-to-Air Heat Pumps: Engineering Data and Installation Manual

Rev.: 21 May 2012D

P/N:



20D085-01NN

Table of Contents:

Section 1: Model Nomenclature
Model Nomenclature2 - 5

Section 2: AHRI Performance Data
Ground Loop & Open Loop 6

Section 3: Physical & Dimensional Data
Compressor Section Data7
MPD Air Handlers8
ACD A-Coils9

Section 4: Electrical Data
Unit Electrical Data 10 - 11

Section 5: Specification Glossary & Calculations
Glossary & Flow Rate Calculations12 - 13

Section 6 Performance Data
Unit Performance Data 14 - 19

Section 7: Installation Introduction
Introduction, Pre-Installation, Components20 - 22

Section 8: Installation
A: Unit Placement23 - 26
B: Filter Drier Installation27
C: Line Set Installation / Charging.....28 - 38
D: Ductwork Installation.....39 - 41

Section 9: Water Quality
Water Quality42

Section 10: Antifreeze
Overview43
Antifreeze Charging44 - 45

Section 11: Controls
Controls & Wiring Diagrams46 - 55

Section 12: Accessories
AP SMA Pump Sharing Module56

Section 13: Troubleshooting
Troubleshooting57 - 64

Section 14: Forms
Troubleshooting, Unit Start-Up, Warranty 65, 67 & 69

Revision Table:

Date	By	Page	Note
22 Oct 2012	GT	35 - 38	Updated Solenoid Coil
21 May 2012	DS	61 - 65	Updated Troubleshooting Data
15 May 2012	DS	51	Updated Wiring Diagram
27 Apr 2012	DS	All	First published




⚠ NOTICE ⚠

**VERY IMPORTANT WARRANTY
REGISTRATION INFORMATION LOCATED
ON THE BACK COVER.**


Enertech Global is continually working to improve its products. As a result, the design and specifications of each product may change without notice and may not be as described herein. For the most up-to-date information, please visit our website, or contact our Customer Service department at info@enertechgeo.com. Statements and other information contained herein are not express warranties and do not form the basis of any bargain between the parties, but are merely Enertech Global's opinion or commendation of its products.

Section 1a: GeoComfort® Model Nomenclature




Rev.: 26 Oct. 2012E

Section 1b: Hydron Module® Model Nomenclature



Rev.: 26 Oct. 2012E


Section 1c: TETCO® Model Nomenclature



Rev.: 26 Oct. 2012E


Section 1d: Air Handler/"A" Coil Model Nomenclature

Air Handlers



Rev.: 11 Oct. 2011E

"A" Coils



Rev.: 14 Sep. 2011E

Section 2: AHRI Performance Data

Ground Loop Heat Pump

MODEL	CAPACITY	HEATING		COOLING	
		Btu/hr	COP	Btu/hr	EER
RT024	Full Load	17,800	3.4	24,600	15.9
	Part Load	14,700	3.9	19,600	23.7
RT036	Full Load	27,200	3.8	36,000	16.7
	Part Load	21,700	4.2	27,800	25.3
RT048	Full Load	36,400	3.9	50,800	18.0
	Part Load	29,800	4.4	39,000	25.4
RT060	Full Load	45,600	3.5	61,500	17.2
	Part Load	37,000	4.1	47,900	24.1



Note:

Rated in accordance with ISO Standard 13256-1 which includes Pump Penalties.


Heating capacities based on 68.0°F DB, 59.0°F WB entering air temperature.

Cooling capacities based on 80.6°F DB, 66.2°F WB entering air temperature.

Entering water temperatures Full Load: 32°F heating / 77°F cooling.

Entering water temperatures Part Load: 41°F heating / 68°F cooling.

Section 3a: Unit Dimensional and Physical Data



Model	Dimensional Data			Refrigeration Connection		Water Loop*		Unit Weight (Pounds)
	Height	Width	Depth	Liquid	Suction	IN	OUT	
024	23.4	32.0	28.8	3/8"	7/8"	1" Double O-Ring		180
036	23.4	32.0	28.8	3/8"	7/8"			225
048	23.4	32.0	28.8	3/8"	7/8"			270
060	23.4	32.0	28.8	1/2"	1-1/8"			270


AHRI Air Handler and "A" Coil Matches

Compressor Section	Air Handler Match	"A" Coil Match
024	MPD024A	ACD024B
036	MPD036A	ACD036B
048	MPD060B	ACD060C
060	MPD060B	ACD060C



⚠ NOTICE ⚠

WHEN MATCHING AN RT048 OR RT060 WITH AN MPD060B, REFER TO THE CFM CHART ON PAGE 50 FOR THE PROPER AIRFLOW JUMPER SETTINGS.

Section 3b: Air Handler Dimensional and Physical Data




Model	Size (tons)	All Dimensions in Inches														
		A	B	C	D	E	F	G	H	J	K	L	M	N	P	R
MPD024A	2	17 5/8	43	21	15 5/8	12 1/2	13 1/2	11	6 3/4	16 3/4	14	11	10 3/4	2	1 1/2	5
MPD036A	3	21 1/8	48	21	19	12 1/2	14 1/2	13	6 3/4	20	17	12 3/4	10 1/4	2 1/4	4 3/8	5
MPD060B	4 - 5	24 5/8	58 7/8	21 3/4	22 1/4	14 1/4	19 3/4	17 1/4	6 3/4	26	23	16 3/4	14 3/8	4 1/4	4 3/8	4 1/2



Return Air Opening		
Model	Width	Depth
MPD024A	15 1/2	19 3/4
MPD036A	19 3/4	19 3/4
MPD060B	23 1/2	20 3/4

Section 3c: “A” Coil Dimensional and Physical Data



Model	Size (tons)	All Dimensions in Inches				
		A	B	C	Liquid	Suction
ACD024B	2	16 5/8	19	14 1/2	3/8	3/4
ACD036B	3	19 5/8	19	18 1/2	3/8	3/4
ACD060C	4 - 6	23 3/4	20 1/2	27 7/8	3/8	7/8

NOTES:

1. The AC series coils are designed as high efficiency “A” coils to be installed on new and existing indoor furnaces. These coils may be used in upflow and downflow applications.
2. Coils are ETL and CSA approved.
3. Primary and secondary drain connections are available on the LH or RH side of the drain pan, and are 3/4” FPT. Center line of drains located from pan corner, 1 1/2” for primary and 3 1/2” for secondary.
4. Drain pan is injection molded high temperature UL approved plastic.
5. All coils are equipped with factory-installed TXV, 15% bleed type.

⚠ WARNING ⚠

IF USING A DUAL FUEL APPLICATION, “A” COIL MUST BE INSTALLED ON THE OUTLET OF THE FURNACE. INSTALLATION ON THE RETURN COULD CAUSE FURNACE HEAT EXCHANGER FAILURE, AND MAY VOID FURNACE WARRANTY.

Section 4a: Unit Electrical Data

Model	Voltage Code	60Hz Power		Compressor		Ext Loop Pump FLA*	Total Unit FLA	Min Circuit AMPS	Max Fuse HACR	Min AWG	Max Ft
		Volts	Phase	LRA	RLA						
024	0	208/230	1	58.3	11.7	4.0	15.7	18.6	30	14	41
	1	208/230	1	58.3	11.7	4.0	15.7	18.6	30	14	41
036	0	208/230	1	83.0	15.3	4.0	19.3	23.1	35	12	51
	1	208/230	1	83.0	15.3	4.0	19.3	23.1	35	12	51
048	0	208/230	1	104.0	21.2	5.5	26.7	32.0	50	8	96
	1	208/230	1	104.0	21.2	5.5	26.7	32.0	50	8	96
060	0	208/230	1	152.9	27.1	5.5	32.6	39.4	60	8	78
	1	208/230	1	152.9	27.1	5.5	32.6	39.4	60	8	78

Notes:

1. All line and low voltage wiring must adhere to the National Electrical Code and Local Codes, whichever is the most stringent.
 2. Wire length based on a one way measurement with a 2% voltage drop.
 3. Wire size based on 60°C copper conductor and minimum circuit ampacity.
 3. All fuses class RK-5
 4. Min/Max Voltage: 208/230/60/1 = 187/252
- * The external loop pump FLA is based on a maximum of three UP26-116F-230V pumps (1/2hp) for 048 - 062 and two pumps for 024 - 038

NOTE: Proper Power Supply Evaluation

When any compressor bearing unit is connected to a weak power supply, starting current will generate a significant “sag” in the voltage which reduces the starting torque of the compressor motor and increases the start time. This will influence the rest of the electrical system in the building by lowering the voltage to the lights. This momentary low voltage causes “light dimming”. The total electrical system should be evaluated with an electrician and HVAC technician. The evaluation should include all connections, sizes of wires, and size of the distribution panel between the unit and the utility’s connection. The transformer connection and sizing should be evaluated by the electric utility provider.

Section 4b: Air Handler Section Unit Electrical Data

Model	60 HZ Power		Field-Installed Elect Heat		Motor Amps / HP	Minimum Circuit Ampacity ²	Maximum Fuse Size ²
	Volts	Phase	# Circuits	kW ¹			
MPD024A	208/230	1	None	0	2.8 / 0.33	3.5	10
			1	10		54.9	60
MPD036A	208/230	1	None	0	4.3 / 0.50	5.4	10
			1	10		56.4	60
			2	15		30.3 / 56.4	40 / 70
MPD060B	208/230	1	None	0	6.8 / 1.0	8.5	15
			1	10		58.9	70
			2	15		32.8 / 58.9	40 / 70
			2	20		58.9 / 58.9	70 / 70

Notes:

1. Nominal kW at 240V. Derate 25% for 208V.
2. Units with field-installed electric heat 15kW and larger have two circuits. Data shown as "XX/XX" refers to circuit 1 before the "/" and circuit 2 after the "/"
3. Always refer to unit nameplate data prior to installation

Section 5: Specification Glossary & Calculations

Glossary of Terms

CFM = Airflow, Cubic Feet/Minute	HR = Total Heat Of Rejection, Btu/hr
COP = Coefficient of Performance = BTU Output / BTU Input	KW = Total Power Unit Input, Kilowatts
EAT = Entering Air Temperature, Fahrenheit (Dry Bulb/Wet Bulb)	LAT = Leaving Air Temperature, Fahrenheit
EER = Energy Efficiency Ratio = BTU output/Watts input	LC = Latent Cooling Capacity, Btu/hr
EWT = Entering Source Water Temperature, Fahrenheit	SC = Sensible Cooling Capacity, Btu/hr
ELT = Entering Load Water Temperature, Fahrenheit	LWT = Leaving Source Water Temperature, Fahrenheit
GPM = Water Flow, Gallons Per Minute	LLT = Leaving Load Water Temperature, Fahrenheit
HC = Total Heating Capacity, Btu/hr	TC = Total Cooling Capacity, Btu/hr
HE = Total Heat Of Extraction, Btu/hr	WPD = Water Pressure Drop, PSI & Feet of Water

Heating & Cooling Calculations

Heating	Cooling
$\text{LAT} = \text{EAT} + \frac{\text{HC}}{\text{CFM} \times 1.08}$	$\text{LAT (DB)} = \text{EAT (DB)} - \frac{\text{SC}}{\text{CFM} \times 1.08}$
$\text{LWT} = \text{EWT} - \frac{\text{HE}}{\text{GPM} \times 500}$	$\text{LWT} = \text{EWT} + \frac{\text{HR}}{\text{GPM} \times 500}$
$\text{LC} = \text{TC} - \text{SC}$	

Section 5: Water Flow Selection

Water Flow Selection

Proper flow rate is crucial for reliable operation of geothermal heat pumps. The performance data shows three flow rates for each entering water temperature (EWT column). The general "rule of thumb" when selecting flow rates is the following:

Top flow rate: Reference low flow rate.

Middle flow rate: Minimum closed loop system flow rate (2.25 to 2.50 gpm/ton)

Bottom flow rate: Nominal (optimum) closed loop system flow rate (3.0 gpm/ton)

Although the "rule of thumb" is adequate in most areas of North America, it is important to consider the application type before applying this "rule of thumb." Antifreeze is generally required for all closed loop (geothermal) applications. Extreme Southern U.S. locations are the only exception. Open loop (well water) systems cannot use antifreeze, and must have enough flow rate in order to avoid freezing conditions at the Leaving Source Water Temperature (LWT) connection.

Calculations must be made for all systems without antifreeze to determine if the top flow rate is adequate to prevent LWT at or near freezing conditions. The following steps should be taken in making this calculation:

Determine minimum EWT based upon your geographical area.

Go to the performance data table for the heat pump model selected and look up the Heat of Extraction (HE) at the "rule of thumb" water flow rate (GPM) and at the design Entering Air Temperature (EAT).

Calculate the temperature difference (TD) based upon the HE and GPM of the model (step 4).

$$TD = HE / (GPM \times 500).$$

Calculate the LWT (step 6).

$$LWT = EWT - TD.$$

If the LWT is below 35-38°F, there is potential for freezing conditions if the flow rate or water temperature is less than ideal conditions, and the flow rate must be increased.

Example 1:

$$EWT = 50^{\circ}\text{F}.$$

3-Ton Model, high capacity. Flow rate = 6.8 GPM. HE = 26,300 Btuh.

$$TD = 26,300 / (6.8 \times 500) = 7.7^{\circ}\text{F}$$

$$LWT = 50 - 7.7 = 42.3^{\circ}\text{F}$$

Water flow rate should be adequate under these conditions.

Example 2:

$$EWT = 40^{\circ}\text{F}.$$

3-Ton Model, high capacity. Flow rate = 6.8 GPM. HE = 22,700 Btuh.

$$TD = 22,700 / (6.8 \times 500) = 6.7^{\circ}\text{F}$$

$$LWT = 40 - 6.7 = 33.3^{\circ}\text{F}$$

Water flow rate must be increased.

Performance Data Notes

1. Capacity data is based upon 15% (by volume) methanol antifreeze solution.
2. Interpolation between above categories is permissible; extrapolation is not.
3. See Flow Rate Selection above for proper application.

Section 6a: Model 024 with MPD024A Performance Data: 2.0 Ton, Full Load, 900 CFM Cooling / 900 CFM Heating

EWT °F	Flow GPM	WPD		Heating						Cooling																			
		PSI	FT	Aiflow CFM	HC MBtuh	HE MBtuh	LAT °F	kW	COP W/W	Aiflow CFM	TC MBtuh	SC MBtuh	S/T	HR MBtuh	kW	EER Btuh/W													
25	6.0	3.7	8.6	900	16.3	11.8	86.8	1.31	3.64	Operation Not Recommended																			
				800	16.2	11.5	88.7	1.36	3.48																				
30	3.0	1.4	3.1	900	16.2	11.8	86.7	1.29	3.68																				
				800	16.1	11.5	88.7	1.34	3.51																				
	4.5	2.3	5.4	900	17.0	12.5	87.5	1.31	3.79																				
				800	16.9	12.2	89.6	1.37	3.62																				
	6.0	3.6	8.4	900	17.8	13.2	88.3	1.34	3.90																				
				800	17.7	13.0	90.5	1.39	3.73																				
40	3.0	1.2	2.8	900	19.2	14.6	89.8	1.35	4.17																				
				800	19.1	14.3	92.1	1.40	3.99																				
	4.5	2.2	5.1	900	20.0	15.3	90.6	1.37	4.27																				
				800	19.9	15.0	93.1	1.43	4.09																				
	6.0	3.5	8.1	900	20.8	16.0	91.4	1.40	4.37																				
				800	20.7	15.8	94.0	1.45	4.19																				
50	3.0	1.1	2.5	900	22.2	17.4	92.8	1.42	4.58														900	28.4	19.9	0.70	33.5	1.50	18.9
				800	22.1	17.1	95.6	1.47	4.39														800	28.0	18.8	0.67	33.2	1.53	18.3
	4.5	2.0	4.7	900	23.0	18.1	93.7	1.44	4.67														900	28.4	19.9	0.70	33.3	1.43	19.9
				800	22.9	17.8	96.5	1.50	4.48														800	28.1	18.8	0.67	33.1	1.46	19.2
	6.0	3.4	7.8	900	23.8	18.8	94.5	1.47	4.75														900	28.5	19.8	0.70	33.2	1.36	20.9
				800	23.7	18.5	97.4	1.52	4.57														800	28.2	18.8	0.67	32.9	1.39	20.2
60	3.0	1.0	2.4	900	25.1	20.0	95.9	1.50	4.90	900	27.5	19.6	0.71	32.9	1.58	17.4													
				800	25.0	19.7	99.0	1.56	4.72	800	27.1	18.6	0.68	32.6	1.61	16.9													
	4.5	1.8	4.2	900	25.9	20.7	96.7	1.53	4.98	900	27.6	19.6	0.71	32.7	1.51	18.3													
				800	25.8	20.4	99.9	1.58	4.80	800	27.2	18.5	0.68	32.5	1.54	17.7													
	6.0	2.8	6.6	900	26.7	21.4	97.5	1.55	5.06	900	27.7	19.6	0.71	32.6	1.44	19.2													
				800	26.6	21.2	100.8	1.60	4.87	800	27.3	18.5	0.68	32.3	1.47	18.6													
70	3.0	0.9	2.1	900	28.0	22.6	98.9	1.60	5.15	900	26.5	19.3	0.73	32.3	1.71	15.5													
				800	27.9	22.3	102.3	1.65	4.97	800	26.1	18.2	0.70	32.0	1.73	15.1													
	4.5	1.7	3.9	900	28.8	23.3	99.7	1.62	5.22	900	26.6	19.2	0.72	32.2	1.64	16.2													
				800	28.7	23.0	103.3	1.67	5.04	800	26.2	18.2	0.69	31.9	1.67	15.7													
	6.0	2.7	6.2	900	29.6	24.0	100.5	1.64	5.29	900	26.7	19.2	0.72	32.0	1.57	17.0													
				800	29.5	23.7	104.2	1.69	5.11	800	26.3	18.1	0.69	31.8	1.60	16.5													
80	3.0	0.8	1.8	900	30.9	25.1	101.8	1.70	5.33	900	25.3	18.9	0.74	31.8	1.88	13.5													
				800	30.8	24.8	105.7	1.75	5.15	800	25.0	17.8	0.71	31.5	1.91	13.1													
	4.5	1.5	3.6	900	31.7	25.8	102.6	1.72	5.40	900	25.4	18.8	0.74	31.6	1.81	14.0													
				800	31.6	25.5	106.6	1.77	5.22	800	25.1	17.7	0.71	31.3	1.84	13.6													
	6.0	2.6	5.9	900	32.5	26.5	103.4	1.74	5.46	900	25.5	18.8	0.74	31.5	1.74	14.6													
				800	32.4	26.3	107.5	1.80	5.28	800	25.1	17.7	0.70	31.2	1.77	14.2													
90	3.0	0.6	1.5	900	33.7	27.5	104.7	1.81	5.45	900	24.0	18.4	0.76	31.2	2.11	11.4													
				800	33.6	27.3	108.9	1.87	5.28	800	23.7	17.3	0.73	30.9	2.14	11.1													
	4.5	1.4	3.2	900	34.5	28.3	105.5	1.84	5.51	900	24.1	18.3	0.76	31.1	2.04	11.8													
				800	34.4	28.0	109.8	1.89	5.34	800	23.7	17.2	0.73	30.8	2.07	11.5													
	6.0	2.4	5.6	900	35.3	29.0	106.3	1.86	5.57	900	24.2	18.3	0.76	30.9	1.97	12.3													
				800	35.2	28.7	110.8	1.91	5.40	800	23.8	17.2	0.72	30.6	2.00	11.9													
100	3.0	0.5	1.2	Operation Not Recommended						900	22.6	17.8	0.79	30.7	2.38	9.5													
										800	22.2	16.7	0.75	30.4	2.41	9.2													
	4.5	1.3	2.9							900	22.6	17.7	0.78	30.5	2.31	9.8													
										800	22.3	16.7	0.75	30.3	2.34	9.5													
	6.0	2.3	5.3							900	22.7	17.7	0.78	30.4	2.24	10.1													
										800	22.4	16.6	0.74	30.1	2.27	9.8													
110	3.0	0.4	0.8	900	20.9	17.1	0.82	30.2	2.70	7.7																			
				800	20.6	16.1	0.78	29.9	2.73	7.5																			
	4.5	1.1	2.6	900	21.0	17.1	0.81	30.0	2.64	8.0																			
				800	20.7	16.0	0.78	29.8	2.66	7.8																			
	6.0	2.2	5.0	900	21.1	17.1	0.81	29.9	2.57	8.2																			
				800	20.7	16.0	0.77	29.6	2.59	8.0																			

Heating data based on 70F EAT; Cooling data based on 80/67F EAT. See Correction Factors on page 19 for different conditions.

**Section 6b: Model 036 with MPD036A Performance Data: 3.0 Ton,
Full Load, 1200 CFM Cooling / 1200 CFM Heating**

EWT °F	Flow GPM	WPD		Heating						Cooling																												
		PSI	FT	Aiflow CFM	HC MBtuh	HE MBtuh	LAT °F	kW	COP W/W	Aiflow CFM	TC MBtuh	SC MBtuh	S/T	HR MBtuh	kW	EER Btuh/W																						
25	9.0	3.5	8.1	1200	26.1	18.1	90.1	2.35	3.25	Operation Not Recommended																												
				1050	25.9	17.6	92.9	2.44	3.11																													
30	4.5	1.4	3.1	1200	26.1	18.1	90.1	2.34	3.27																													
				1050	25.9	17.6	92.8	2.42	3.13																													
	6.8	2.2	5.2	1200	27.1	19.0	90.9	2.37	3.36																													
				1050	26.9	18.5	93.7	2.45	3.21																													
9.0	3.4	7.9	1200	28.1	20.0	91.7	2.39	3.44																														
			1050	27.9	19.5	94.6	2.48	3.30																														
40	4.5	1.2	2.8	1200	30.1	21.8	93.2	2.43	3.63																													
				1050	29.9	21.3	96.4	2.52	3.48																													
	6.8	2.1	4.9	1200	31.1	22.7	94.0	2.46	3.71																													
				1050	30.9	22.2	97.3	2.55	3.56																													
9.0	3.3	7.7	1200	32.1	23.7	94.8	2.49	3.79																														
			1050	32.0	23.2	98.2	2.57	3.64																														
50	4.5	1.1	2.5	1200	34.1	25.4	96.3	2.54	3.93																							1200	35.0	23.1	0.66	42.4	2.19	16.0
				1050	33.9	24.9	99.9	2.63	3.78																							1050	34.6	22.1	0.64	42.0	2.16	16.0
	6.8	2.0	4.6	1200	35.1	26.3	97.1	2.57	4.01																							1200	34.8	22.9	0.66	41.9	2.09	16.6
				1050	34.9	25.9	100.8	2.65	3.85																							1050	34.4	21.8	0.63	41.5	2.07	16.7
9.0	3.2	7.4	1200	36.1	27.3	97.9	2.60	4.08	1200																							34.6	22.6	0.65	41.4	2.00	17.3	
			1050	36.0	26.8	101.7	2.68	3.93	1050																							34.2	21.6	0.63	41.0	1.97	17.3	
60	4.5	1.1	2.6	1200	38.1	29.0	99.4	2.66	4.19	1200	36.3	24.3	0.67	44.1	2.29	15.8																						
				1050	37.9	28.5	103.4	2.75	4.03	1050	35.9	23.3	0.65	43.7	2.26	15.9																						
	6.8	1.8	4.2	1200	39.1	29.9	100.2	2.69	4.25	1200	36.1	24.1	0.67	43.6	2.20	16.4																						
				1050	38.9	29.4	104.3	2.78	4.10	1050	35.7	23.0	0.64	43.1	2.17	16.5																						
9.0	2.7	6.3	1200	40.1	30.8	101.0	2.72	4.32	1200	35.9	23.8	0.67	43.0	2.10	17.0																							
			1050	39.9	30.3	105.2	2.81	4.17	1050	35.5	22.8	0.64	42.6	2.08	17.1																							
70	4.5	1.0	2.2	1200	42.0	32.4	102.4	2.81	4.39	1200	36.8	25.1	0.68	45.1	2.44	15.0																						
				1050	41.8	31.9	106.9	2.89	4.24	1050	36.4	24.1	0.66	44.7	2.42	15.1																						
	6.8	1.7	3.9	1200	43.0	33.4	103.2	2.83	4.45	1200	36.6	24.9	0.68	44.6	2.35	15.5																						
				1050	42.9	32.9	107.8	2.92	4.30	1050	36.2	23.8	0.66	44.2	2.32	15.6																						
9.0	2.6	6.0	1200	44.1	34.3	104.0	2.86	4.51	1200	36.3	24.6	0.68	44.1	2.26	16.1																							
			1050	43.9	33.8	108.7	2.95	4.36	1050	36.0	23.6	0.65	43.6	2.23	16.1																							
80	4.5	0.8	1.9	1200	45.9	35.8	105.5	2.96	4.54	1200	36.5	25.4	0.70	45.5	2.65	13.7																						
				1050	45.8	35.3	110.3	3.05	4.40	1050	36.1	24.4	0.68	45.1	2.63	13.8																						
	6.8	1.5	3.5	1200	47.0	36.8	106.2	2.99	4.60	1200	36.2	25.2	0.70	45.0	2.56	14.2																						
				1050	46.8	36.3	111.3	3.08	4.45	1050	35.9	24.1	0.67	44.6	2.53	14.2																						
9.0	2.4	5.7	1200	48.0	37.7	107.0	3.02	4.66	1200	36.0	24.9	0.69	44.5	2.47	14.6																							
			1050	47.8	37.2	112.2	3.11	4.51	1050	35.7	23.9	0.67	44.0	2.44	14.6																							
90	4.5	0.7	1.5	1200	49.9	39.2	108.5	3.14	4.66	1200	35.3	25.3	0.72	45.3	2.91	12.1																						
				1050	49.7	38.7	113.8	3.22	4.52	1050	35.0	24.3	0.69	44.9	2.88	12.1																						
	6.8	1.4	3.2	1200	50.9	40.1	109.3	3.16	4.71	1200	35.1	25.1	0.71	44.8	2.82	12.5																						
				1050	50.7	39.6	114.7	3.25	4.57	1050	34.8	24.0	0.69	44.3	2.79	12.5																						
9.0	2.3	5.3	1200	51.9	41.0	110.1	3.19	4.76	1200	34.9	24.8	0.71	44.2	2.73	12.8																							
			1050	51.7	40.5	115.6	3.28	4.62	1050	34.6	23.8	0.69	43.8	2.70	12.8																							
100	4.5	0.5	1.2	Operation Not Recommended						1200	33.4	24.8	0.74	44.4	3.22	10.4																						
										1050	33.1	23.7	0.72	44.0	3.20	10.4																						
	6.8	1.2	2.9							1200	33.2	24.5	0.74	43.9	3.13	10.6																						
										1050	32.9	23.5	0.71	43.5	3.10	10.6																						
9.0	2.2	5.0	1200							33.0	24.3	0.74	43.4	3.04	10.9																							
			1050							32.7	23.2	0.71	43.0	3.01	10.9																							
110	4.5	0.4	0.9							1200	30.7	23.8	0.77	43.0	3.59	8.6																						
										1050	30.4	22.8	0.75	42.6	3.56	8.5																						
	6.8	1.1	2.5							1200	30.5	23.6	0.77	42.5	3.49	8.7																						
										1050	30.2	22.5	0.75	42.0	3.47	8.7																						
9.0	2.0	4.6	1200	30.3	23.3	0.77	41.9	3.40	8.9																													
			1050	30.0	22.3	0.74	41.5	3.37	8.9																													

Heating data based on 70F EAT; Cooling data based on 80/67F EAT. See Correction Factors on page 19 for different conditions.

**Section 6c: Model 048 with MPD060B Performance Data: 4.0 Ton,
Full Load, 1650 CFM Cooling / 1600 CFM Heating**

EWT °F	Flow GPM	WPD		Heating						Cooling												
		PSI	FT	Aiflow CFM	HC MBtuh	HE MBtuh	LAT °F	kW	COP W/W	Aiflow CFM	TC MBtuh	SC MBtuh	S/T	HR MBtuh	kW	EER Btuh/W						
25	12.0	5.5	12.7	1600	33.8	23.7	89.6	2.94	3.36	Operation Not Recommended												
				1350	33.5	23.0	93.0	3.07	3.19													
30	6.0	2.0	4.6	1600	34.5	24.4	90.0	2.95	3.43													
				1350	34.2	23.7	93.5	3.08	3.26													
	9.0	3.5	8.1	1600	35.7	25.6	90.7	2.98	3.51													
				1350	35.4	24.8	94.3	3.10	3.34													
	12.0	5.4	12.6	1600	36.9	26.7	91.4	3.00	3.60													
				1350	36.6	25.9	95.1	3.13	3.43													
40	6.0	1.9	4.3	1600	40.1	29.7	93.2	3.06	3.84													
				1350	39.8	28.9	97.3	3.19	3.66													
	9.0	3.3	7.7	1600	41.3	30.8	93.9	3.09	3.92													
				1350	41.0	30.0	98.1	3.21	3.74													
	12.0	5.3	12.2	1600	42.5	31.9	94.6	3.11	4.01													
				1350	42.2	31.2	98.9	3.24	3.82													
50	6.0	1.7	3.9	1600	44.9	34.1	96.0	3.15	4.17							1650	55.6	39.0	0.70	64.9	2.74	20.3
				1350	44.6	33.4	100.6	3.28	3.98							1400	54.2	36.1	0.67	63.6	2.74	19.8
	9.0	3.2	7.4	1600	46.1	35.3	96.7	3.18	4.25							1650	55.9	38.9	0.70	64.9	2.62	21.3
				1350	45.8	34.5	101.4	3.30	4.06							1400	54.6	36.1	0.66	63.5	2.62	20.8
	12.0	5.1	11.9	1600	47.3	36.4	97.4	3.21	4.32							1650	56.3	38.9	0.69	64.8	2.49	22.5
				1350	47.0	35.6	102.2	3.33	4.13							1400	54.9	36.1	0.66	63.4	2.49	22.0
60	6.0	1.7	3.9	1600	48.8	37.8	98.3	3.23	4.42	1650	54.2	38.4	0.71	64.0	2.88	18.8						
				1350	48.5	37.0	103.3	3.36	4.23	1400	52.9	35.6	0.67	62.7	2.88	18.4						
	9.0	3.0	6.9	1600	50.0	38.9	99.0	3.26	4.50	1650	54.6	38.4	0.70	64.0	2.75	19.8						
				1350	49.7	38.1	104.1	3.38	4.30	1400	53.2	35.5	0.67	62.6	2.75	19.3						
	12.0	4.6	10.7	1600	51.2	40.0	99.6	3.28	4.57	1650	54.9	38.3	0.70	63.9	2.63	20.9						
				1350	50.9	39.3	104.9	3.41	4.37	1400	53.6	35.5	0.66	62.5	2.63	20.4						
70	6.0	1.6	3.7	1600	51.9	40.6	100.0	3.30	4.61	1650	52.5	37.7	0.72	63.1	3.09	17.0						
				1350	51.6	39.9	105.4	3.42	4.41	1400	51.2	34.8	0.68	61.7	3.09	16.6						
	9.0	2.9	6.7	1600	53.1	41.8	100.7	3.33	4.68	1650	52.9	37.6	0.71	63.0	2.97	17.8						
				1350	52.8	41.0	106.2	3.45	4.48	1400	51.5	34.8	0.68	61.7	2.97	17.4						
	12.0	4.5	10.5	1600	54.3	42.9	101.4	3.35	4.75	1650	53.2	37.6	0.71	62.9	2.85	18.7						
				1350	54.0	42.1	107.0	3.48	4.55	1400	51.9	34.8	0.67	61.6	2.84	18.2						
80	6.0	1.5	3.5	1600	54.1	42.7	101.3	3.35	4.73	1650	50.5	36.8	0.73	62.1	3.39	14.9						
				1350	53.8	41.9	106.9	3.48	4.53	1400	49.2	34.0	0.69	60.8	3.39	14.5						
	9.0	2.8	6.5	1600	55.3	43.8	102.0	3.38	4.80	1650	50.9	36.8	0.72	62.0	3.27	15.6						
				1350	55.0	43.0	107.7	3.50	4.60	1400	49.5	33.9	0.68	60.7	3.27	15.2						
	12.0	4.5	10.3	1600	56.5	44.9	102.7	3.40	4.87	1650	51.2	36.7	0.72	61.9	3.15	16.3						
				1350	56.2	44.2	108.5	3.53	4.67	1400	49.9	33.9	0.68	60.6	3.14	15.9						
90	6.0	1.4	3.3	1600	55.5	43.9	102.1	3.39	4.80	1650	48.2	35.8	0.74	61.1	3.78	12.8						
				1350	55.2	43.2	107.8	3.51	4.60	1400	46.9	33.0	0.70	59.8	3.78	12.4						
	9.0	2.7	6.3	1600	56.7	45.1	102.8	3.41	4.87	1650	48.5	35.8	0.74	61.0	3.65	13.3						
				1350	56.4	44.3	108.7	3.54	4.67	1400	47.2	32.9	0.70	59.7	3.65	12.9						
	12.0	4.4	10.1	1600	57.9	46.2	103.5	3.44	4.93	1650	48.9	35.7	0.73	60.9	3.53	13.9						
				1350	57.6	45.4	109.5	3.56	4.73	1400	47.5	32.9	0.69	59.6	3.53	13.5						
100	6.0	1.3	3.1	Operation Not Recommended						1650	45.6	34.7	0.76	60.0	4.24	10.7						
										1400	44.2	31.8	0.72	58.7	4.24	10.4						
	9.0	2.6	6.1							1650	45.9	34.6	0.75	60.0	4.12	11.1						
										1400	44.6	31.8	0.71	58.6	4.12	10.8						
	12.0	4.3	9.9							1650	46.2	34.6	0.75	59.9	3.99	11.6						
										1400	44.9	31.7	0.71	58.5	3.99	11.2						
110	6.0	1.2	2.9	Operation Not Recommended						1650	42.6	33.4	0.78	59.0	4.79	8.9						
										1400	41.3	30.5	0.74	57.6	4.79	8.6						
	9.0	2.5	5.9							1650	42.9	33.3	0.78	58.9	4.67	9.2						
										1400	41.6	30.5	0.73	57.5	4.66	8.9						
	12.0	4.2	9.7							1650	43.3	33.3	0.77	58.8	4.54	9.5						
										1400	41.9	30.4	0.73	57.4	4.54	9.2						

Heating data based on 70F EAT; Cooling data based on 80/67F EAT. See Correction Factors on page 19 for different conditions.

**Section 6d: Model 060 with MPD060B Performance Data: 5.0 Ton,
Full Load, 1950 CFM Cooling / 1900 CFM Heating**

EWT °F	Flow GPM	WPD		Heating						Cooling													
		PSI	FT	Aiflow CFM	HC MBtuh	HE MBtuh	LAT °F	kW	COP W/W	Aiflow CFM	TC MBtuh	SC MBtuh	S/T	HR MBtuh	kW	EER Btuh/W							
25	15.0	9.8	22.7	1900	43.5	30.1	91.2	3.92	3.25	Operation Not Recommended													
				1800	43.2	29.6	92.2	3.99	3.17														
30	7.5	3.4	7.8	1900	43.7	30.4	91.3	3.90	3.28														
				1800	43.4	29.9	92.3	3.97	3.20														
	11.3	6.1	14.0	1900	45.3	31.9	92.1	3.94	3.37														
				1800	45.0	31.4	93.2	4.01	3.29														
	15.0	9.7	22.4	1900	46.9	33.4	92.9	3.97	3.46														
				1800	46.6	32.9	94.0	4.04	3.38														
40	7.5	3.1	7.2	1900	50.3	36.6	94.5	4.01	3.68														
				1800	50.0	36.1	95.7	4.08	3.59														
	11.3	5.8	13.3	1900	51.9	38.1	95.3	4.04	3.76														
				1800	51.6	37.6	96.5	4.12	3.67														
	15.0	9.4	21.7	1900	53.5	39.6	96.1	4.08	3.84														
				1800	53.2	39.0	97.4	4.15	3.76														
50	7.5	2.8	6.6	1900	56.4	42.3	97.5	4.13	4.00								1950	67.4	46.0	0.68	79.4	3.50	19.3
				1800	56.1	41.8	98.9	4.20	3.91								1800	66.5	44.3	0.67	78.5	3.50	19.0
	11.3	5.5	12.7	1900	58.0	43.8	98.3	4.17	4.08								1950	67.5	46.0	0.68	79.0	3.36	20.1
				1800	57.7	43.3	99.7	4.24	3.99								1800	66.7	44.3	0.66	78.1	3.36	19.9
	15.0	9.1	21.1	1900	59.6	45.3	99.1	4.20	4.16								1950	67.7	46.0	0.68	78.7	3.22	21.0
				1800	59.4	44.8	100.5	4.28	4.07								1800	66.8	44.3	0.66	77.8	3.21	20.8
60	7.5	2.6	6.0	1900	62.1	47.5	100.3	4.27	4.26	1950	66.1	45.5	0.69	78.5	3.64	18.2							
				1800	61.8	47.0	101.8	4.34	4.17	1800	65.3	43.8	0.67	77.7	3.63	18.0							
	11.3	4.9	11.3	1900	63.7	49.0	101.1	4.31	4.34	1950	66.3	45.6	0.69	78.2	3.49	19.0							
				1800	63.4	48.5	102.6	4.38	4.25	1800	65.4	43.8	0.67	77.3	3.49	18.7							
	15.0	8.0	18.5	1900	65.3	50.5	101.8	4.34	4.41	1950	66.4	45.6	0.69	77.9	3.35	19.8							
				1800	65.1	50.0	103.5	4.41	4.32	1800	65.6	43.9	0.67	77.0	3.35	19.6							
70	7.5	2.5	5.7	1900	67.4	52.3	102.8	4.42	4.46	1950	64.4	44.9	0.70	77.6	3.86	16.7							
				1800	67.1	51.7	104.5	4.49	4.37	1800	63.5	43.2	0.68	76.7	3.86	16.5							
	11.3	4.8	11.1	1900	69.0	53.8	103.6	4.46	4.53	1950	64.5	44.9	0.70	77.2	3.72	17.3							
				1800	68.7	53.2	105.3	4.53	4.44	1800	63.7	43.2	0.68	76.4	3.72	17.1							
	15.0	7.9	18.2	1900	70.6	55.3	104.4	4.50	4.60	1950	64.7	44.9	0.69	76.9	3.58	18.1							
				1800	70.3	54.7	106.2	4.57	4.51	1800	63.8	43.2	0.68	76.0	3.58	17.8							
80	7.5	2.3	5.4	1900	72.2	56.5	105.2	4.59	4.61	1950	62.2	44.0	0.71	76.5	4.19	14.9							
				1800	71.9	56.0	107.0	4.66	4.52	1800	61.3	42.2	0.69	75.6	4.18	14.7							
	11.3	4.7	10.8	1900	73.8	58.0	106.0	4.63	4.67	1950	62.3	44.0	0.71	76.1	4.04	15.4							
				1800	73.5	57.5	107.8	4.70	4.59	1800	61.4	42.3	0.69	75.2	4.04	15.2							
	15.0	7.8	17.9	1900	75.4	59.5	106.8	4.66	4.74	1950	62.4	44.0	0.70	75.8	3.90	16.0							
				1800	75.1	59.0	108.7	4.73	4.65	1800	61.6	42.3	0.69	74.9	3.90	15.8							
90	7.5	2.2	5.1	1900	76.6	60.3	107.3	4.77	4.70	1950	59.5	42.8	0.72	75.2	4.60	12.9							
				1800	76.3	59.8	109.3	4.84	4.62	1800	58.6	41.1	0.70	74.3	4.60	12.7							
	11.3	4.6	10.5	1900	78.2	61.8	108.1	4.81	4.77	1950	59.6	42.8	0.72	74.8	4.46	13.4							
				1800	77.9	61.3	110.1	4.88	4.68	1800	58.7	41.1	0.70	73.9	4.46	13.2							
	15.0	7.6	17.6	1900	79.8	63.3	108.9	4.85	4.83	1950	59.7	42.8	0.72	74.5	4.32	13.8							
				1800	79.5	62.8	110.9	4.92	4.74	1800	58.9	41.1	0.70	73.6	4.32	13.6							
100	7.5	2.1	4.9	Operation Not Recommended						1950	56.3	41.4	0.74	73.7	5.11	11.0							
										1800	55.4	39.7	0.72	72.8	5.11	10.8							
	11.3	4.4	10.2							1950	56.4	41.4	0.73	73.4	4.97	11.4							
										1800	55.5	39.7	0.72	72.5	4.96	11.2							
	15.0	7.5	17.4							1950	56.5	41.5	0.73	73.0	4.83	11.7							
										1800	55.7	39.7	0.71	72.1	4.82	11.5							
110	7.5	2.0	4.6	1950	52.6	39.8	0.76	72.1	5.71	9.2													
				1800	51.7	38.1	0.74	71.2	5.71	9.1													
	11.3	4.3	10.0	1950	52.7	39.8	0.76	71.7	5.57	9.5													
				1800	51.8	38.1	0.73	70.8	5.57	9.3													
	15.0	7.4	17.1	1950	52.9	39.8	0.75	71.4	5.43	9.7													
				1800	52.0	38.1	0.73	70.5	5.42	9.6													

Heating data based on 70F EAT; Cooling data based on 80/67F EAT. See Correction Factors on page 19 for different conditions.

Section 6k: Performance Data Correction Factors

Heating Correction Factors

EAT °F	HC	HE	kW
50	1.0450	1.1136	0.8208
55	1.0347	1.0893	0.8567
60	1.0260	1.0640	0.9019
65	1.0089	1.0270	0.9497
70	1.0000	1.0000	1.0000
75	0.9924	0.9741	1.0527
80	0.9870	0.9653	1.0522

Cooling Correction Factors

EAT (WB) °F	TC	HR	kW
55	0.8215	0.8293	0.8635
60	0.8955	0.9001	0.9205
63	0.9404	0.9431	0.9547
65	0.9701	0.9715	0.9774
67	1.0000	1.0000	1.0000
70	1.0446	1.0425	1.0335
75	1.1179	1.1124	1.0878

Sensible Cooling Correction Factors

EAT (WB) °F	EAT (DB) °F				
	70	75	80	85	90
55	1.201	1.289			
60	0.943	1.067	1.192		
63	0.852	0.995	1.138		
65	0.797	0.952	1.106	1.261	
67	0.624	0.812	1.000	1.188	1.343
70		0.697	0.820	0.944	1.067
75			0.637	0.817	0.983

Section 7: Installation Introduction

INTRODUCTION

This geothermal heat pump provides forced air heating and cooling. Engineering and quality control is built into every geothermal unit. Good performance depends on proper application and correct installation.

Notices, Cautions, Warnings, & Dangers

“NOTICE” Notification of installation, operation or maintenance information which is important, but which is NOT hazard-related.

“CAUTION” Indicates a potentially hazardous situation or an unsafe practice which, if not avoided, COULD result in minor or moderate injury or product or property damage.

“WARNING” Indicates potentially hazardous situation which, if not avoided, COULD result in death or serious injury.

“DANGER” Indicates an immediate hazardous situation which, if not avoided, WILL result in death or serious injury.

Inspection

Upon receipt of any geothermal equipment, carefully check the shipment against the packing slip and the freight company bill of lading. Verify that all units and packages have been received. Inspect the packaging of each package and each unit for damages. Insure that the carrier makes proper notation of all damages or shortage on all bill of lading papers. Concealed damage should be reported to the freight company within 15 days. If not filed within 15 days the freight company can deny all claims.

Note: Notify Enertech Global's shipping department of all damages within 15 days. It is the responsibility of the purchaser to file all necessary claims with the freight company.

Unit Protection

Protect units from damage and contamination due to plastering (spraying), painting and all other foreign materials that may be used at the job site. Keep all units covered on the job site with either the original packaging or equivalent protective covering. Cap or recap

unit connections and all piping until unit is installed. Precautions must be taken to avoid physical damage and contamination which may prevent proper start-up and may result in costly equipment repair.

CAUTION

DO NOT OPERATE THE GEOTHERMAL HEAT PUMP UNIT DURING BUILDING CONSTRUCTION PHASE.

Storage

All geothermal units should be stored inside in the original packaging in a clean, dry location. Units should be stored in an upright position at all times. Units should not be stacked unless specially noted on the packaging.

WARNING

FAILURE TO FOLLOW THIS CAUTION MAY RESULT IN PERSONAL INJURY. USE CARE AND WEAR APPROPRIATE PROTECTIVE CLOTHING, SAFETY GLASSES AND PROTECTIVE GLOVES WHEN SERVICING UNIT AND HANDLING PARTS.

Section 7: Installation Introduction

Consumer Instructions: Dealer should instruct the consumer in proper operation, maintenance, filter replacements, thermostat and indicator lights. Also provide the consumer with the manufacturer's Owner's Manual for the equipment being installed.

Enertech Global D-I-Y Policy: Enertech Global's geothermal heat pumps and system installations may include electrical, refrigerant and/or water connections. Federal, state and local codes and regulations apply to various aspects of the installation. Improperly installed equipment can lead to equipment failure and health/safety concerns. For these reasons, only qualified technicians should install a Enertech Global built geothermal system.

Because of the importance of proper installation, Enertech Global does not sell equipment direct to homeowners. Internet websites and HVAC outlets may allow for purchases directly by homeowners and do-it-yourselfers, but Enertech Global offers no warranty on equipment that is purchased via the internet or installed by persons without proper training.

Enertech Global has set forth this policy to ensure installations of Enertech Global geothermal systems are done safely and properly. The use of well-trained, qualified technicians helps ensure that your system provides many years of comfort and savings.

Equipment Installation: Special care should be taken in locating the unit. All units should be placed on a formed plastic air pad, or a high density pad slightly larger than the base of the unit.

Electrical: All wiring, line and low voltage, should comply with the manufacturer's recommendations, The National Electrical Code, and all local codes and ordinances.

Thermostat: Thermostats should be installed approximately 54 inches off the floor on an inside wall in the return air pattern and where they are not in direct sunlight at anytime.

Loop Pumping Modules: Must be wired to the heat pump's electric control box. A special wiring whip is provided to connect the Pump Module wiring.

Components

Master Contactor: Energizes Compressor and optional Hydronic Pump package.

Logic Board: Logic Board operates the compressor and protects unit by locking out when safety switches are engaged. It also provides fault indicator(s).

Terminal Strip: Provides connection to the thermostat or other accessories to the low voltage circuit.

Transformer: Converts incoming (source) voltage to 24V AC.

Low Voltage Breaker: Attached directly to transformer, protects the transformer and low voltage circuit.

Reversing Valve: Controls the cycle of the refrigerant system (heating or cooling). Energized in cooling mode.

High Pressure Switch: Protects the refrigerant system from high refrigerant pressure, by locking unit out if pressure exceeds setting.

Low Pressure Switch: Protects the refrigerant system from low suction pressure, if suction pressure falls below setting.

Flow Switch (Freeze Protection Device): Protects the water heat exchanger from freezing, by shutting down compressor if water flow decreases.

Compressor (Copeland Scroll): Pumps refrigerant through the heat exchangers and pressurizes the refrigerant, which increases the temperature of the refrigerant.

Section 7: Installation Introduction

Pre-Installation


Special care should be taken in locating the geothermal unit. Installation location chosen should include adequate service clearance around the unit.

Pre-Installation Steps:

1. Compare the electrical data on the unit nameplate with packing slip and ordering information to verify that the correct unit has been shipped.
2. Inspect all electrical connections and wires. Connections must be clean and tight at the terminals, and wires should not touch any sharp edges or copper pipe.
3. Verify that all refrigerant tubing is free of dents and kinks. Refrigerant tubing should not be touching other unit components.
4. Before unit start-up, read all manuals and become familiar with unit components and operation. Thoroughly check the unit before operating.
5. Verify that all components of the system will have adequate service access.
6. Make sure that all applicable wiring, ductwork, piping, and accessories are correct and on the job site.
7. Verify that the air handler or "A" coil selected for the system is the correct AHRI match for the selected outdoor unit.
8. For A-Coil installations, it is recommended that coil be sprayed with liquid detergent thoroughly and rinsed thoroughly before installation to assure proper drainage of condensate from the coil fins to eliminate water blowoff and to assure maximum coil performance. If not sprayed approximately 50 hours of break in time is required to achieve the same results.
9. Unpack all components of the outdoor installation kit, which is located in a separate box shipped with the unit. The kit should contain the following.
 - 1 Flow Center Cover
 - 2 Aluminum Pipe Shield
 - 3 Pre-Assembled Hose Kit with P/T Ports
 - 4 Pump Wiring Harness
 - 5 PE 90° Street Elbows
(Shown with field provided piping)

⚠ WARNING ⚠

IF USING A DUAL FUEL APPLICATION, "A" COIL MUST BE INSTALLED ON THE OUTLET OF THE FURNACE. INSTALLATION ON THE RETURN COULD CAUSE FURNACE HEAT EXCHANGER FAILURE, AND MAY VOID FURNACE WARRANTY.



⚠ CAUTION ⚠

BEFORE DRILLING OR DRIVING ANY SCREWS INTO CABINET, CHECK TO BE SURE THE SCREW WILL NOT HIT ANY INTERNAL PARTS OR REFRIGERANT LINES.

Section 8a: Unit Placement

Site Preparation

First, survey the installation site to determine the best location for placing the outdoor unit. The outdoor unit must be installed no closer than 9 inches from the outdoor walls of the facility.

Ground level installations must be located according to local codes or ordinances. A suitable mounting pad must be used and it must be separate from the building foundation. The pad must be level and strong enough to support the weight of the unit. The pad height must be a minimum of 2 inches above grade and with adequate drainage.

An electrical disconnect must be located within sight of the unit and readily accessible. The electrical disconnect shall be capable of electrically de-energizing the outdoor unit. All electrical connections must be made in accordance with all applicable codes and ordinances. See electrical data tables for correct wire and fuse sizing.

Unit Preparation

Carefully remove all unit packaging and pallet fasteners that are located on two corners of the unit. Again inspect the unit for any damage to the cabinet or service valves.

Unit Placement/Lifting Unit

Once the site is ready for unit placement, the compressor section can be moved by lifting from the bottom of the unit. Do not lift the unit by placing your hand under the control box section, or by using the snow load bars, this could deform the unit and cause damage.

Once the unit is in-place, and oriented for both line set and loop connections, remove both the top cover and the control box cover.

Unit Top Cover Removal

To remove the unit top cover, remove the two screws on the front end of the top cover. Once the screws are removed, pull the lid slightly up, and then forward to disengage the rear retainer clips. Take care not to lift directly up as you may warp the retainer clips and cause the cover to not seat properly.

Example 1: Outdoor Unit Placement



Example 2: Outdoor Unit Placement



Control Box Cover Removal

To remove the control box cover, remove the four screws on both sides of the cover. The control box cover is designed to be removed whether the unit top cover is installed or not. However, if the unit top cover is installed, it might be slightly difficult to remove due to the gasketing that protects the control box from moisture. Take care with removal or replacement to not damage this gasketing.

Section 8a: Unit Placement

Flow Center Installation

Once the unit is in-place, and the unit cover and control box cover is removed, the flow center can now be installed

The flow center is installed on the outside of the unit and is designed to hang over the unit pad. It is necessary to rotate the flow center to keep the flush valves between the loop and the pumps. Before installing the flow center, the pump(s) will need to be rotated on the flow center where the electrical box is in the upward direction (Figure 1). Failure to reorientate the pumps could lead to condensation entering the electrical box of the pump potentially causing unit damage. Once the pumps are rotated, the flow center can be attached to the cabinet with four provided screws.

After the flow center is mounted on the unit, the provided wire harness which connects the flow center to the control section can be attached (Figure 2).

Once the pumps are wired and connected, install the provided hose kit to connect the flow center to the unit. The hoses are clearly labeled loop in and loop out. The hose kits are designed so that the 90° elbows with the PT ports are installed on the flow center side. All models utilize double o-ring fittings for hose kit connection. Make sure all connections are solid and retainer rings are secure and hand tight.

Freeze Sensor

A built-in freeze protection system energizes the flow center pumps to circulate the loop fluid when the cabinet temperature is below 22°F. The pumps are disengaged when the cabinet temperatures is above 32°F. (The switch has a tolerance of +/- 3°F)

Figure 1: Flow Center Installation





Figure 2: Flow Center Wiring



Section 8a: Unit Placement

Loop Connection

The RT is designed around making loop connection easy. Once the flow center is in-place, it's time to bring the loop to the unit.

After the loop has been installed and headered, the supply and return lines should be trenched to the side of the unit where the flow center is located. At this point, you have a couple of options on connecting the loop to the flow center.

Option 1:

The loop can be brought directly into the bottom of the flow center using the double o-ring to PE fusion fitting included with the flow center (Figure 3). This might be slightly difficult depending on how much play you have with the piping and area to work in.

Option 2:

The loop can be brought at an angle into the bottom of the flow center. Included with the installation kit are 2 90° PE street elbows. These should be fused to the double o-ring to PE fusion fitting included with the flow center. From there, you can use an extension of PE pipe and another 90° elbow to make the final connection. The aluminum pipe shield and outdoor cover have been designed with extra room to accommodate this option (Figure 4). If this option is installed above grade, the total assembly cannot exceed 9" to fit inside the pipe shield.

Loop Flushing

Once all loop and unit piping is completed, flush and fill the loop using normal procedures outlined in the Loop & Flow Center AOM (PN# 2323-0027-001). See the water quality (Section 9) and antifreeze overview and charging (Section 10) sections in this document for additional information.

Figure 3: Straight Loop Connection





Figure 4: Angled Loop Connection



Pipe Shield

Once the loop installation is completed, the pipe shield can be installed. This aluminum shield will protect the loop lines from damage.

To install the shield, you may have to clear out a small amount of dirt around the loop piping. The shield has notches and a guide for proper placement. The goal is to have the shield slightly buried to insure proper protection.

Section 8a: Unit Placement

Line Set Installation

The RT model features angled backseating service valves for line set installation. See Section 9b for proper procedures for installation of the line set and unit charging.

Unit Wiring

Line voltage to the unit should be supplied from a dedicated branch circuit containing the correct fuse or circuit breaker for the unit. The outdoor unit requires both power and control circuit electrical connections. All electrical connections must be in accordance with all applicable codes and ordinances.

Line voltage to the unit must be protected and brought into the unit through the bottom of the control box. Wires should be attached to the L1 and L2 terminals of the contactor, and to ground. See electrical data tables for correct wire and fuse sizing for each unit.

Unit Assembly

Once the following installation items are completed, use the Unit Startup form in this manual to begin final unit startup.

1. Flow center installed, loop field connected, hose kit connection, unit and loop field flushed and filled.
2. Line and low voltage wiring completed.
3. Line set installed at the unit and at the air handler or "A" coil.
4. Unit fully charged and ready for operation.


Once the final startup has been completed and the unit is operating properly, replace all panels and covers in the following order.

1. **Flow center cover.** The flow center cover locks into place with clips on the left side and screws along the top to secure the cover to the unit. The cover should fit over the aluminum pipe shield.
2. **Control Box Cover.** The control box cover secures to the cabinet with four screws.
3. **Top Unit Cover.** Place the unit cover clip first onto the back of the unit. Keeping the cover at about a 10° angle to the top of the unit, slide the cover back to engage the clips. Once the clips are engaged, lower the lid down and replace the two front screws to finish securing the lid.

Figure 5: Service Valves



Figure 6: Control Box



Section 8b: Filter Drier Installation

INSTALLATION

A reversible heat pump filter drier must be installed on the liquid line near the cabinet of the compressor section. A filter drier is furnished with the unit. The filter drier kit includes a 3" piece of 1/2" or 5/8" copper tubing. This tubing will fit either inside or on the outside of the stub coming off the liquid line service valve. Braze it in place. Then braze the filter drier onto it. Make sure the arrow on the filter drier points in the appropriate direction. A second piece of copper is attached between the filter drier and the liquid line (not needed for all applications, depending upon line set size -- consult line set sizing chart).

Refer to the split system I.O.M. (installation, operating, and maintenance) manual for details on line set and unit installation. Always use dry nitrogen when brazing.

Table 1: Recommended Line Set Sizes


Model	Unit Refrigerant Connections		Recommended Liquid & Suction Line Size			
			20 Feet		50 Feet	
	Liquid Line (OD)	Suction Line (OD)	Liquid Line (OD)	Suction Line* (OD)	Liquid Line (OD)	Suction Line (OD)
024	3/8	7/8	3/8	7/8	Two-stage unit's line sizes should not be increased due to reduced pumping capacity in first stage.	
036	3/8	7/8	3/8	7/8		
048	3/8	7/8	3/8	7/8		
060	1/2	1-1/8	1/2	1-1/8		

40°F Evaporating Temperature

*Suction line is not sized large in two-stage units due to the lower velocity of first stage operation.

Weight of refrigerant in copper lines per 10 feet	
Liquid Line Size (OD)	Oz. Per 10 Feet
3/8"	5.4
1/2"	10.4
5/8"	19.5

Figure 7: Filter Drier Installation



Section 8c: Line Set Installation

INTRODUCTION

The purpose of this section is to help in the design of refrigeration line sets on geothermal heat pump systems. The three considerations when designing a refrigerant piping system are as follows:

1. **System Reliability:** Poor Oil Management may shorten the life of the compressor. Proper liquid refrigerant control is essential.
2. **System Performance:** Pressure drop in refrigerant lines tends to decrease capacity and increase power consumption. High velocities can increase sound levels. Modulation often depends on proper piping.
3. **Cost:** Level of refrigerant, copper piping, accessories, and labor used will impact the applied cost.

DEFINITIONS

Long line set applications are defined as any line set that includes 50 feet or more of interconnecting tubing or a vertical distance between the evaporator and compressor sections exceeding 20 feet.

LINE SET REQUIREMENTS/LIMITATIONS

Line Set Limitations

Up to 50 equivalent feet: Use rated line sizes listed in unit installation instructions.

50 - 75 equivalent feet or 20 feet of vertical separation: Bi-flow liquid line solenoid and crankcase heater required (refer to figures 12-15 on pages 35-38).

Maximum Piping Lengths:

Maximum equivalent length = 75 feet

Maximum linear length = 50 feet

Maximum linear liquid lift = 50 feet

Maximum linear vapor rise =

50 feet (Single Speed)/25 feet (Two Stage)

FITTINGS AND COMPONENTS

All piping should be "ACR" or "L" type copper pipe. Long radius fittings should always be used unless there is not enough physical space. Pressure drop due to friction in pipe, fittings

and field installed accessories such as a drier, solenoid valve or other devices should be considered (see Table 2). The pressure drop due to friction is usually smaller than pressure drop due to lift. The pressure drop ratings of field installed devices are usually supplied by the manufacturer of the device and should be used if available.

Equivalent Length

Valves, fittings, and bends create more friction pressure drop than straight copper piping. Find the equivalent feet of straight tubing for each fitting for calculations. This allows for a quick calculation of the total equivalent length (see Example 1). The equivalent length of copper tubing for commonly used fittings, valves, and filter-drier are shown in Table 2.

Total Equivalent Length = Linear Feet of Straight Tubing + Fitting Losses in Equivalent Feet

Example 1: A 3-ton unit with 7/8" vapor tubing has 50 linear feet of straight tubing. The total number of elbows includes three long radius 90° elbows and five standard 90° elbows.

50ft. of straight tubing
 + 4 standard 90° elbows X 2 equiv ft
 + 1 liquid line solenoid X 12 equiv ft
 + 1 filter-drier X 6 equiv ft
 = 50ft. + 8ft. + 12ft. + 6ft.
 = 76 ft. total equivalent length

Table 2: Copper Fittings in Equivalent Length

Tube Size O.D. (in.)	90° Std A	90° Long Radius - B	45° Std C	45° Long Radius
3/8"	1.2	0.8	0.5	0.3
1/2"	1.3	0.9	0.6	0.4
5/8"	1.6	1.0	0.8	0.5
3/4"	1.8	1.2	0.9	0.6
7/8"	2.0	1.4	1.0	0.7
1-1/8"	2.6	1.7	1.3	0.9
Liquid Line Solenoid	12			
Filter	6			

Section 8c: Line Set Installation

LINE SETS

Vapor Line

A long line set application can critically increase the charge level needed for a system. As a result, the system is very prone to refrigerant migration during its off-cycle. A crankcase heater and bi-flow liquid line solenoid will help minimize this risk. A crankcase heater and bi-flow liquid line solenoid is recommended for any line set over 50 feet in equivalent length or 20 feet of vertical separation. Because oil separates from the refrigerant in the evaporator, the vapor line velocity must be adequate to carry the oil along with the refrigerant. Horizontal vapor lines require a minimum of 800 fpm velocity for oil entrainment. Vapor risers require 1200 fpm minimum, and preferably 1500 fpm regardless of the length of the riser.

NOTE: When a two-stage compressor section is located above the indoor coil, the maximum vertical rise of a vapor line must not exceed 25 feet. This limit is due to velocity requirements for oil entrainment in the vapor riser.


For example, a 4 ton unit producing 48,000 Btuh with a 7/8" vapor line has a velocity of 1500 fpm (See Figure 9). On first stage the compressor runs at 67% or 32,680 Btuh and has a velocity of less than 1200 fpm per the pressure drop chart. In order to achieve velocity up to 1500 fpm in first stage, the line would have to be 3/4". The pressure drop for 48,000 Btuh would be over 9 psi. A system will lose approximately 1% capacity for every pound of pressure drop due to friction in the suction line. This 1% factor is used to estimate the capacity loss of refrigerant lines. Due to the low velocities created in the vapor line in first stage, a two stage unit vapor line should not be increased from the pipe size at the compressor section.

For all vapor line trapping see Figure 8. Remember to add all the fittings into the total equivalent length of the vapor line.

Liquid Line


Pressure drop due to vertical liquid lift must be considered. The pressure drop for vertical lift is 0.43 pound per foot for R-410A. This is usually large and may be a limiting factor in the ultimate design of the system. Next, the pressure entering the expansion device must be sufficient to produce the required flow through the expansion device. A pressure drop of 175 psi for R-410A across the expansion valve and distributor is necessary to produce full refrigerant flow at rated capacity. Therefore, it is necessary for liquid refrigerant (free of flash gas) to be delivered to the expansion valve. Longer line sets may require a larger liquid line due to the higher pressure drops of smaller diameter tubing. Reference the Installation Manual for recommended liquid line sizes for each unit. Even liquid lines on two stage units can be increased because velocities required for oil return are not critical in the liquid line.

Figure 8: Oil Trap Construction



Section 8c: Line Set Installation

Figure 9: Refrigerant R-410A Suction Line Pressure Drop/Velocity per 100 ft. of Line at 45°F Evaporating Temperature and 125°F Condensing Temperature



To use this chart, first find capacity (tons) on the left side of the chart. To find pipe size, proceed right to the smallest pipe size. Pressure drop (vertical line) and velocity (diagonal lines) can then be determined for the pipe size selected. For example, for a 4 ton unit, select 7/8" O.D. line.

NOTE: Shaded area denotes unacceptable velocity range.

Section 8c: Line Set Installation

GEOTHERMAL REFRIGERATION CIRCUITS

Bi-Flow Liquid Line Solenoid Valve

In order to minimize off-cycle refrigerant migration to the compressor, a bi-flow liquid line solenoid is required for all long line set heat pump applications. The Bi-flow solenoid valve controls the flow of refrigerant only in the direction of the arrow molded into the valve. The bi-flow liquid line solenoid valve is shipped as a single flow valve, the carton contains another valve stem which needs to be installed in the valve to convert it to a bi-flow valve. The bi-flow valve should be connected to the 24V side of the contactor. When installing the valve, **the arrow should be positioned toward the compressor section** to minimize the transfer of liquid directly into the coax in the heating mode. The solenoid should be installed right after the filter-drier or within two feet of the compressor section.

Charging Information

Since the lengths of line sets vary, it is necessary to calculate additional refrigerant charge. Compressor sections do not have additional charge for the line set. Each foot of liquid line and vapor length requires the amount of refrigerant designated in Table 3. Also, long line applications require a minimum of 10 degrees subcooling to prevent any refrigerant flashing before the thermostatic expansion valve. The subcooling and superheat should be checked in both modes of operation. Refer to the operating pressure chart in the Specifications manual for the correct superheat.

PIPING DIAGRAMS

The piping diagrams on the following pages illustrate considerations for applications of a solenoid valve, traps, and piping based upon the location of the compressor section and air handler.

Table 3: Refrigerant Weight

Weight of Refrigerant in Copper Tubing Per Foot (in Ounces)		
O.D. (in.)	Liquid Line	Suction (Vapor) Line
3/8"	0.54	
1/2"	1.04	
5/8"	1.95	0.07
3/4"		0.10
7/8"		0.13
1-1/8"		0.21

Section 8c: Line Set Installation

SPLIT SYSTEM CHARGING - APPROACH METHOD

Charging Enertech split systems can easily be accomplished by measuring approach temperatures when operating in the cooling mode. This method, outlined in the steps below, is based upon testing in Enertech's R & D labs with matched compressor/air handler or A-coil components. For best results, the indoor temperature should be between 70°F and 85°F in cooling. Charging the unit in cooling is the most accurate method. If unable to charge the unit in cooling mode, refer to the next section, "Split System Charging -- Subcooling/Superheat Method." Refer to figure 6 for temperature and pressure measurement locations when using the approach method.

Please Note: Before utilizing the approach method for checking the system charge, confirm the system reaches a minimum of 2°F subcooling, while maintaining a maximum of 22°F superheat. If you are not able to achieve these readings, further troubleshooting will be required (Reference Table 12 in Section 13, Refrigeration Troubleshooting). Consult the Refrigeration/Troubleshooting manual for a review of Superheat/Subcooling calculations.

1. If the entering water temperature is above 45°F and the entering air temperature is above 70°F, the unit should be charged in cooling for the most accurate results. If the return air temperature is below 70°F, it may be necessary to run the system in emergency heating mode to raise the indoor temperature above 70°F.
2. Evacuate the line set and A-coil. Open the service valves, and monitor the system pressures while charging. Model 024 is charged with 36oz; model 036 is charged with 56oz; and models 048 - 072 are charged with 80oz. This factory charge is a "starting" supply. Charge will need to be added for the line set and heat exchangers. However, do not add charge until the unit has run for at least five minutes, and the subcooling is above 2°F (see step #3).
3. The approach temperatures will not be usable if there is not a liquid lock at the liquid line (i.e. there is some subcooling at the liquid line). Record the liquid line

pressure and the saturation temperature (most gauge sets show saturation temperature on the gauge). Measure the liquid line temperature. If the liquid line is not at least 2°F cooler than the liquid line saturation temperature, there may not be a liquid lock. Continue to add charge until subcooling reaches at least 2°F. Then, proceed to step #4.

4. Measure the water flow rate and entering water temperature (EWT). Measure the liquid line temperature (using the same digital thermometer if possible).
5. Subtract the EWT from the liquid line temperature (LLT) to determine approach temperature (Approach temperature = LLT - EWT).
6. Compare the result to Table 4. If the approach temperature is too high, add charge; if it's too low, recover charge. Approach temperature should be within 1°F of the table value.

SPLIT SYSTEM CHARGING - SUBCOOLING/ SUPERHEAT METHOD

If checking charge in the heating mode (**preferred charging mode is cooling**), follow the steps below. For best results, the indoor temperature should be between 60°F and 70°F in heating. If the return air temperature is below 60°F, it may be necessary to run the system in emergency heating mode to raise the indoor temperature above 60°F. Refer to figure 7 for temperature and pressure measurement locations when using the Subcooling/Superheat method.

1. Evacuate the line set and A-coil. Open the service valves, and monitor the system pressures while charging. The compressor section is charged for the compressor section and air handler/A-coil only (except model 024, which includes about 65% of this charge for manufacturing process reasons). Charge will need to be added for the line set (and heat exchangers for model 024). However, do not add charge until the unit has run for at least five minutes, and the subcooling is above 2°F (see step #2).
2. The system will not be stable if there is not a liquid lock at the liquid line (i.e. there is some subcooling at the liquid line). Record the liquid line pressure and the saturation

Section 8c: Line Set Installation


Table 4: Approach Temperatures-Cooling Mode*

Full Load Operation

Water Flow GPM/ton	Entering Water Temp., deg F	Entering Air DB Temp., deg F	Approach Temp. by Model, deg. F Full Load			
			024	036	048	060
1.5	45	70 - 85	6	5	18	8
	55		6	6	15	7
	65		5	5	12	5
	75		4	4	9	3
	85		3	3	6	2
2.25	55	70 - 85	4	2	13	4
	65		4	3	10	4
	75		3	3	7	3
	85		2	2	5	1
	95		1	2	2	1
3.0	55	70 - 85	3	1	11	3
	65		3	2	9	3
	75		2	2	6	2
	85		1	2	4	1
	95		1	1	2	1

*Cooling approach temperature = Liquid Line temp - Entering Water temp
(should be within +/- 1 deg F)

Figure 10: Cooling Mode -- Temperature & Pressure Measurement Locations



NOTE: Check water flow via pressure drop method (pressurized systems) or flow meter tool (non-pressurized systems). Compare water flow to chart in Table 2.

Section 8c: Line Set Installation

temperature (most gauge sets show saturation temperature on the gauge). Measure the liquid line temperature at the air handler. If the liquid line is not at least 2°F cooler than the liquid line saturation temperature (i.e. 2°F Subcooling), there may not be a liquid lock. Continue to add charge until subcooling reaches at least 2°F. Then, proceed to step #3.


- Record the suction pressure and the saturation temperature (most gauge sets show saturation temperature on the gauge). Measure the suction line temperature. If the suction line temperature is more than 15°F higher than the saturation temperature (i.e. 15°F Superheat), the unit is undercharged.
- Continue to add charge to the unit, comparing the Superheat/Subcooling results to Table 5. Stop adding charge when the Superheat/Subcooling values are within range. Each time the refrigerant charge is adjusted, allow at least five minutes run time for the system to stabilize.

Table 5: Subcooling/Superheat-Heating Mode*
Full Load Operation

Model	Entering Water Temp., deg. F	Entering Air Temp., deg. F	Subcooling	Superheat
024	32	60 - 70	3 - 5	8 - 10
	40		2 - 4	9 - 11
	50		2 - 4	9 - 11
036	32	60 - 70	7 - 9	5 - 7
	40		7 - 9	5 - 7
	50		7 - 9	5 - 7
048	32	60 - 70	4 - 6	6 - 8
	40		4 - 6	7 - 9
	50		4 - 6	9 - 11
060	32	60 - 70	2 - 4	4 - 6
	40		3 - 5	5 - 7
	50		6 - 8	5 - 7


*Valid for flow rates between 1.5 and 3 GPM/ton.

Figure 11: Heating Mode -- Temperature & Pressure Measurement Locations



Section 8c: Line Set Installation

Figure 12: Air handler section above compressor section




Notes:

- A Bi-flow liquid line solenoid required if total equivalent length is greater than or equal to 50 feet or the vertical separation is greater than or equal to 20 feet. See tables below for descriptions and part numbers.
- An inverted vapor line trap must be installed with the top of the trap above the evaporator section.
- P-traps should be installed at the outlet of the evaporator section and at the bottom of vapor line drop.
- 75 feet maximum equivalent line length
- 50 feet maximum vertical separation
- Vapor Line sizes on Two-stage units should not be increased due to the velocity requirements for returning oil to the compressor.

Bi-flow Solenoid Data		
Compatible Models	Description	Part Number
All Split Models (24-60)	1/2" Valve Body	ARS-4A
	24V Coil	ARSCB
	Bi-flow kit	ARSBK
Only required in long line set applications. All three parts must be ordered.		

Section 8c: Line Set Installation

Figure 13: Compressor section above air handler section




Notes:

- A Bi-flow liquid line solenoid required if total equivalent length is greater than or equal to 50 feet or the vertical separation is greater than or equal to 20 feet. See tables below for descriptions and part numbers.
- A P-trap should be installed at the outlet of the evaporator section.
- If vertical separation is greater than or equal to 50 feet a second trap should be installed at the 50 feet mark.
- 75 feet maximum equivalent line length
- 50 feet maximum vertical separation
- Vapor Line sizes on Two-stage units should not be increased due to the velocity requirements for returning oil to the compressor.
- Two-stage units should have a maximum of 25 feet of vertical lift on the vapor line.

Bi-flow Solenoid Data		
Compatible Models	Description	Part Number
All Split Models (24-60)	1/2" Valve Body	ARS-4A
	24V Coil	ARSCB
	Bi-flow kit	ARSBK
Only required in long line set applications. All three parts must be ordered.		

Section 8c: Line Set Installation

Figure 14: Horizontal piping above air handler section




Notes:

- A Bi-flow liquid line solenoid required if total equivalent length is greater than or equal to 50 feet or the vertical separation is greater than or equal to 20 feet. See tables below for descriptions and part numbers.
- The vapor line must be installed with the horizontal run higher than the top of the evaporator section.
- P-traps should be installed at the outlet of the evaporator section and at the bottom of vapor line drop.
- 75 feet maximum equivalent line length
- 50 feet maximum vertical separation
- Vapor Line sizes on Two-stage units should not be increased due to the velocity requirements for returning oil to the compressor.

Bi-flow Solenoid Data		
Compatible Models	Description	Part Number
All Split Models (24-60)	1/2" Valve Body	ARS-4A
	24V Coil	ARSCB
	Bi-flow kit	ARSBK
Only required in long line set applications. All three parts must be ordered.		

Section 8c: Line Set Installation

Figure 15: Horizontal piping above “A” coil



Notes:

- A Bi-flow liquid line solenoid required if total equivalent length is greater than or equal to 50 feet or the vertical separation is greater than or equal to 20 feet. See tables below for descriptions and part numbers.
- The vapor line must be installed with the horizontal run higher than the top of the evaporator section.
- P-traps should be installed at the outlet of the evaporator section and at the bottom of vapor line drop.
- 75 feet maximum equivalent line length
- 50 feet maximum vertical separation
- Vapor Line sizes on Two-stage units should not be increased due to the velocity requirements for returning oil to the compressor.

Bi-flow Solenoid Data		
Compatible Models	Description	Part Number
All Split Models (24-60)	1/2" Valve Body	ARS-4A
	24V Coil	ARSCB
	Bi-flow kit	ARSBK
Only required in long line set applications. All three parts must be ordered.		

⚠ WARNING ⚠

IF USING A DUAL FUEL APPLICATION, "A" COIL MUST BE INSTALLED ON THE OUTLET OF THE FURNACE. INSTALLATION ON THE RETURN COULD CAUSE FURNACE HEAT EXCHANGER FAILURE, AND MAY VOID FURNACE WARRANTY.

Section 8d: Ductwork Installation

DUCT WORK

All new ductwork shall be designed as outlined in Sheet Metal and Air Conditioning Contractors National Association (SMACNA) or Air Conditioning Contractors of America (ACCA) or American Society of Heating, Refrigerating and Air Conditioning Engineers (ASHRAE) handbooks.

All supply/return plenums should be isolated from the unit by a flexible connector (canvas) or equivalent to prevent transfer of vibration noise to the ductwork. The flex connector should be designed so as not to restrict airflow. Turning vanes should be used on any run over 500 CFM. If the unit is installed in a noninsulated space the metal ductwork should be insulated on the inside with fiberglass insulation or similar insulation to prevent heat loss/gain and to absorb air noise. If the unit is being installed with existing ductwork, the ductwork must be designed to handle the air volume required by the unit being installed. When running a cooling or heating load on a building, size ductwork accordingly to the building design load and heat pump CFM.

Rule of Thumb: When sizing ductwork use 400 CFM per Ton.

As a general rule, maximum recommended face velocity for a supply outlet used in a residential application is 800 FPM. Maximum recommended return grille velocity is 400 FPM. Systems with higher velocity, are likely to have noise problems.


In buildings where ceilings are 8 feet or more, at least 50 percent of the return air should be taken back to the heat pump from the ceiling or high sidewall location and not more than 50 percent from the floor or low sidewall location.

⚠ NOTICE ⚠

WHEN MATCHING AN RT048 OR RT060 WITH AN MPD060B, REFER TO THE CFM CHART ON PAGE 50 FOR THE PROPER AIRFLOW JUMPER SETTINGS.

Section 8d: Ductwork Installation

Figure 16: Standard Ductwork Connection Setup




The air handling unit comes with an ECM blower motor. For maximum performance, the blower speed should be set to maintain between 350 and 450 CFM/ton. Changing the wires (for PSC) at the blower will change the blower speed.

Table 6: Maximum Air Velocities

Location	Supply	Return
Main Ducts	900 FPM	600 FPM
Branch Ducts	700 FPM	600 FPM
Grills, Registers, Diffusers	750 FPM	600 FPM

Section 8d: Ductwork Installation

Figure 17: Ductwork with Split Damper Connection Setup



Section 9: Unit Piping Installation

Water Quality

The quality of the water used in geothermal systems is very important. In closed loop systems the dilution water (water mixed with antifreeze) must be of high quality to ensure adequate corrosion protection. Water of poor quality contains ions that make the fluid “hard” and corrosive. Calcium and magnesium hardness ions build up as scale on the walls of the system and reduce heat transfer. These ions may also react with the corrosion inhibitors in glycol based heat transfer fluids, causing them to precipitate out of solution and rendering the inhibitors ineffective in protecting against corrosion. In addition, high concentrations of corrosive ions, such as chloride and sulfate, will eat through any protective layer that the corrosion inhibitors form on the walls of the system.

Ideally, de-ionized water should be used for dilution with antifreeze solutions since de-

ionizing removes both corrosive and hardness ions. Distilled water and zeolite softened water are also acceptable. Softened water, although free of hardness ions, may actually have increased concentrations of corrosive ions and, therefore, its quality must be monitored. It is recommended that dilution water contain less than 100 PPM calcium carbonate or less than 25 PPM calcium plus magnesium ions; and less than 25 PPM chloride or sulfate ions.

In an open loop system the water quality is of no less importance. Due to the inherent variation of the supply water, it should be tested prior to making the decision to use an open loop system. Scaling of the heat exchanger and corrosion of the internal parts are two of the potential problems. The Department of Natural Resources or your local municipality can direct you to the proper testing agency. Please see Table 7 for guidelines.

Table 7: Water Quality

Potential Problem	Chemical(s) or Condition	Range for Copper Heat Exchangers	Range for Cupro-Nickel Heat Exchangers
Scaling	Calcium & Magnesium Carbonate	Less than 350 ppm	Less than 350 ppm
Corrosion	pH Range	7 - 9	5 - 9
	Total Dissolved Solids	Less than 1000 ppm	Less than 1500 ppm
	Ammonia, Ammonium Hydroxide	Less than 0.5 ppm	Less than 0.5 ppm
	Ammonium Chloride, Ammonium Nitrate	Less than 0.5 ppm	Less than 0.5 ppm
	Calcium Chloride / Sodium Chloride	Less than 125 ppm	Less than 125 ppm - Note 4
	Chlorine	Less than 0.5 ppm	Less than 0.5 ppm
Biological Growth	Hydrogen Sulfide	None Allowed	None Allowed
	Iron Bacteria	None Allowed	None Allowed
	Iron Oxide	Less than 1 ppm	Less than 1 ppm
Erosion	Suspended Solids	Less than 10 ppm	Less than 10 ppm
	Water Velocity	Less than 8 ft/s	Less than 12 ft/s

Notes:

1. Hardness in ppm is equivalent to hardness in mg/l
2. Grains/gallon = ppm divided by 17.1
3. Copper and cupro-nickel heat exchangers are not recommended for pool applications for water outside the range of the table. Secondary heat exchangers are required for applications not meeting the requirements shown above.
4. Saltwater applications (approx. 25,000 ppm) require secondary heat exchangers due to copper piping between the heat exchanger and the unit fittings.

Section 10: Antifreeze

Antifreeze Overview

In areas where minimum entering loop temperatures drop below 40°F, or where piping will be routed through areas subject to freezing, antifreeze is required. Alcohols and glycols are commonly used as antifreeze. However, local and state/provincial codes supersede any instructions in this document. The system needs antifreeze to protect the coaxial heat exchanger from freezing and rupturing. Freeze protection should be maintained to 15°F below the lowest expected entering source loop temperature. For example, if 30°F is the minimum expected entering source loop temperature, the leaving source loop temperature could be 22 to 25°F. Freeze protection should be set at 15°F (30-15 = 15°F). To determine antifreeze requirements, calculate how much volume the system holds. Then, calculate how much antifreeze will be needed by determining the percentage of antifreeze required for proper freeze protection. See Tables 9 and 10 for volumes and percentages. The freeze protection should be checked during installation using the proper hydrometer to measure the specific gravity and freeze protection level of the solution.

Antifreeze Characteristics

Selection of the antifreeze solution for closed loop systems require the consideration of many important factors, which have long-term implications on the performance and life of the equipment. Each area of concern leads to a different "best choice" of antifreeze. *There is no "perfect" antifreeze.* Some of the factors to consider are as follows (Brine = antifreeze solution including water):

Safety: The toxicity and flammability of the brine (especially in a pure form).

Cost: Prices vary widely.

Thermal Performance: The heat transfer and viscosity effect of the brine.

Corrosiveness: The brine must be compatible with the system materials.

Stability: Will the brine require periodic change out or maintenance?

Convenience: Is the antifreeze available and easy to transport and install?

Codes: Will the brine meet local and state/provincial codes?

The following are some general observations about the types of brines presently being used:

Methanol: Wood grain alcohol that is considered toxic in pure form. It has good heat transfer, low viscosity, is non-corrosive, and is mid to low price. The biggest down side is that it is flammable in concentrations greater than 25%.

Ethanol: Grain alcohol, which by the ATF (Alcohol, Tobacco, Firearms) department of the U.S. government, is required to be denatured and rendered unfit to drink. It has good heat transfer, mid to high price, is non-corrosive, non-toxic even in its pure form, and has medium viscosity. It also is flammable with concentrations greater than 25%. Note that the brand of ethanol is very important. Make sure it has been formulated for the geothermal industry. Some of the denaturants are not compatible with HDPE pipe (for example, solutions denatured with gasoline).

Propylene Glycol: Non-toxic, non-corrosive, mid to high price, poor heat transfer, high viscosity when cold, and can introduce micro air bubbles when adding to the system. It has also been known to form a "slime-type" coating inside the pipe. Food grade glycol is recommended because some of the other types have certain inhibitors that react poorly with geothermal systems. A 25% brine solution is a minimum required by glycol manufacturers, so that bacteria does not start to form.

Ethylene Glycol: Considered toxic and is not recommended for use in earth loop applications.

GS4 (POTASSIUM ACETATE): Considered highly corrosive (especially if air is present in the system) and has a very low surface tension, which causes leaks through most mechanical fittings. This brine is not recommended for use in earth loop applications.

Section 10: Antifreeze

Notes:

1. Consult with your representative or distributor if you have any questions regarding antifreeze selection or use.
2. All antifreeze suppliers and manufacturers recommend the use of either de-ionized or distilled water with their products.

Antifreeze Charging

Calculate the total amount of pipe in the system and use Table 9 to calculate the amount of volume for each specific section of the system. Add the entire volume together, and multiply that volume by the proper antifreeze percentage needed (Table 9) for the freeze protection required in your area. Then, double check calculations during installation with the proper hydrometer and specific gravity chart (Figure 18) to determine if the correct amount of antifreeze was added.

Table 8: Pipe Fluid Volume

Type	Size	Volume Per 100ft US Gallons
Copper	1" CTS	4.1
Copper	1.25" CTS	6.4
Copper	1.5" CTS	9.2
HDPE	.75" SDR11	3.0
HDPE	1" SDR11	4.7
HDPE	1.25" SDR11	7.5
HDPE	1.5" SDR11	9.8
HDPE	2" SDR11	15.4

Additional component volumes:

Unit coaxial heat exchanger = 1 Gallon

Flush Cart = 8-10 Gallons

10' of 1" Rubber Hose = 0.4 Gallons

⚠ CAUTION ⚠

USE EXTREME CARE WHEN OPENING, POURING, AND MIXING FLAMMABLE ANTIFREEZE SOLUTIONS. REMOTE FLAMES OR ELECTRICAL SPARKS CAN IGNITE UNDILUTED ANTIFREEZES AND VAPORS. USE ONLY IN A WELL VENTILATED AREA. DO NOT SMOKE WHEN HANDLING FLAMMABLE SOLUTIONS. FAILURE TO OBSERVE SAFETY PRECAUTIONS MAY RESULT IN FIRE, INJURY, OR DEATH. NEVER WORK WITH 100% ALCOHOL SOLUTIONS.

Section 10: Antifreeze


Table 9 Antifreeze Percentages by Volume

Type of Antifreeze	Minimum Temperature for Freeze Protection			
	10°F (-12.2°C)	15°F (-9.4°C)	20°F (-6.7°C)	25°F (-3.9°C)
ProCool (Ethanol)	25%	22%	17%	12%
Methanol	25%	21%	16%	10%
Propylene Glycol	38%	30%	22%	15%

All antifreeze solutions are shown in pure form - not premixed

NOTE: Most manufacturers of antifreeze solutions recommend the use of de-ionized water. Tap water may include chemicals that could react with the antifreeze solution.

Figure 18: Antifreeze Specific Gravity



Section 11: Controls

MICROPROCESSOR FEATURES AND OPERATION

EnerTech Global geothermal heat pump controls provide a unique modular approach for controlling heat pump operation. The control system uses one, two, or three printed circuit boards, depending upon the features of a particular unit. This approach simplifies installation and troubleshooting, and eliminates features that are not applicable for some units. Split units include only the lockout board in the compressor section.

A microprocessor-based printed circuit board controls the inputs to the unit as well as outputs for status mode, faults, and diagnostics. A status LED and an LED for each fault is provided for diagnostics. Removable low voltage terminal strips provide all necessary terminals for field connections.

Startup/Random Start

The unit will not operate until all the inputs and safety controls are checked for normal conditions. At first power-up, the compressor is energized after a five minute delay. In addition, a zero to sixty second random start delay is added at first power-up to avoid multiple units from being energized at the same time.

Short Cycle Protection

A built-in five minute anti-short cycle timer provides short cycle protection of the compressor.

Component Sequencing Delays

Components are sequenced and delayed for optimum space conditioning performance and to make any startup noise less noticeable.

Test Mode

The microprocessor control allows the technician to shorten most timing delays for faster diagnostics by changing the position of a jumper located on the lockout board.

Water Solenoid Valve Connections

Two accessory relay outputs at the terminal strip provide a field connection for two types of water solenoid valves, a standard 24VAC solenoid valve, or a 24VAC solenoid valve with an end switch. Additional field wiring is no longer required for operation of the end switch.

Loop Pump Circuit Breakers (Single Compressor Units)

The loop pump(s) are protected by control box mounted circuit breakers for easy wiring of pumps during installation. Circuit breakers eliminate the need to replace fuses.

Safety Controls

The control receives separate signals for high pressure, low pressure, low water flow, and condensate overflow faults. Upon a continuous 30-second measurement of the fault (immediate for high pressure), compressor operation is suspended (see Fault Retry below), and the appropriate LED flashes. Once the unit is locked out (see Fault Retry below), an output (terminal "L") is made available to a fault LED at the thermostat (water-to-water unit has fault LED on the corner post).

Low Pressure: If the low pressure switch is open for 30 continuous seconds, the compressor operation will be interrupted, and the control will go into fault retry mode. At startup, the low pressure switch is not monitored for 90 seconds to avoid nuisance faults.

High Pressure: If the high pressure switch opens, the compressor operation will be interrupted, and the control will go into fault retry mode. There is no delay from the time the switch opens and the board goes into fault retry mode. There is also no delay of switch monitoring at startup.

Flow Switch: If the flow switch is open for 30 continuous seconds, the compressor operation will be interrupted, and the control will go into fault retry mode. At startup, the flow switch is not monitored for 30 seconds to avoid nuisance faults.

FAULT RETRY

All faults are retried twice before finally locking the unit out. The fault retry feature is designed to prevent nuisance service calls. There is an anti-short cycle period between fault retries. On the third fault, the board will go into lockout mode.

Section 11: Controls

Over/Under Voltage Shutdown

The lockout board protects the compressor from operating when an over/under voltage condition exists. The control monitors secondary voltage (24VAC) to determine if an over/under voltage condition is occurring on the primary side of the transformer. For example, if the secondary voltage is 19 VAC, the primary voltage for a 240V unit would be approximately 190V, which is below the minimum voltage (197V) recommended by the compressor manufacturer. This feature is self-resetting. If the voltage comes back within range, normal operation is restored. Therefore, over/under voltage is not a lockout.

Under voltage (18 VAC) causes the compressor to disengage and restart when the voltage returns to 20 VAC. Over voltage (31 VAC) causes the compressor to disengage and restart when the voltage returns to 29 VAC. During an over or under voltage condition, all five fault LEDs will blink (HP + LP + FS + CO + Status). When voltage returns to normal operation, the four fault LED's will stop blinking, but the status LED will continue to flash. While the board LEDs are flashing, the thermostat fault light will be illuminated.

Intelligent Reset

If the thermostat is powered off and back on (soft reset), the board will reset, but the last fault will be stored in memory for ease of troubleshooting. If power is interrupted to the board, the fault memory will be cleared.

Diagnostics

The lockout board includes five LEDs (status, high pressure, low pressure, low water flow, condensate overflow) for fast and simple control board diagnosis. On the following page is a table showing LED function.

NOTE: Condensate overflow is not used for split systems. Any condensate overflow protection must be added to the air handler.

Lockout Board Jumper Selection

The lockout board includes three jumpers for field selection of various board features.

Water Solenoid Valve Delay (WSD): When the WSD jumper is installed, the "A" terminal is energized when the compressor is energized. When the jumper is removed, the "A" terminal is energized 10 seconds after the compressor. If using the Taco water solenoid valve (or a valve with an end switch), the unit terminal strip includes a means for connecting a valve of this type. The WSD jumper should be installed. If using a fast opening valve that does not have an end switch, the jumper should be removed.

Test Mode (TEST): When the TEST jumper is installed, the board operates in the normal mode. When the jumper is removed, the board operates in test mode, which speeds up all delays for easier troubleshooting. When service is complete, the jumper must be re-installed in order to make sure that the unit operates with normal sequencing delays.

Over/Under Voltage Disable (O/V): When the O/V jumper is installed, the over/under voltage feature is active. When the jumper is removed, the over/under voltage feature is disabled. On rare occasions, variations in voltage will be outside the range of the over/under voltage feature, which may require removal of the jumper. However, removal of the jumper could cause the unit to run under adverse conditions, and therefore should not be removed without contacting technical services. An over/under voltage condition could cause premature component failure or damage to the unit controls. Any condition that would cause this fault must be thoroughly investigated before taking any action regarding the jumper removal. Likely causes of an over/under voltage condition include power company transformer selection, insufficient entrance wire sizing, defective breaker panel, incorrect transformer tap (unit control box), or other power-related issues.

Section 11: Controls

Table 10: LED Identification

LED Color	Location ¹	Function	Normal Operation	Fault Retry ²	Lockout ²
Green	Top	High Pressure	OFF	Flashing ³	ON ³
Orange	2nd	Low Pressure	OFF	Flashing ³	ON ³
Red	3rd	Water Flow	OFF	Flashing ³	ON ³
Yellow	4th	Condensate* Overflow	OFF	Flashing ³	ON ³
Green	Bottom	Status	Flashing ⁴	Flashing ⁵	Flashing ⁴

Notes:

1. Looking at the board when the LEDs are on the right hand side
 2. If all five lights are flashing, the fault is over/under voltage
 3. Only the light associated with the particular fault/lockout will be on or flashing.
For example, if a high pressure lockout has occurred, the top green light will be on.
The orange, red, and yellow lights will be off
 4. Status lights will be off when in test mode
 5. Flashes alternately with the fault LED
- * Not applicable in split units

SEQUENCE OF OPERATION

Water-to-Air Units, Single Compressor, ECM Fan

Heating, 1st Stage (Y1,G)

The ECM fan is started immediately at 75% (of 1st stage operation) CFM level, first stage compressor and the loop pump(s) are energized 10 seconds after the "Y1" input is received, and the ECM fan adjusts to 100% (of 1st stage operation) CFM level 30 seconds after the "Y1" input.

Heating, 2nd Stage (Y1,Y2,G)

The ECM fan adjusts to 2nd stage CFM level, and the compressor full load solenoid valve is energized.

Heat, 3rd Stage (Y1,Y2,W,G)

The ECM fan remains at 100% of 2nd stage CFM level, and the electric backup heat is energized.

Emergency Heat (W,G)

The fan is started immediately at 100% of 2nd stage CFM level, and the electric backup heat is energized.

Cooling Operation

The reversing valve is energized for cooling operation. Terminal "O" from the thermostat is connected to the reversing valve solenoid.

Cooling, 1st stage (Y1,O,G) Two-Stage Units

The ECM fan is started immediately at 75% (of 1st stage operation) CFM level, first stage compressor and the loop pump(s) are energized 10 seconds after the "Y1" input is received, and the ECM fan adjusts to 100% (of 1st stage operation) CFM level 30 seconds after the "Y1" input.

Cooling, 2nd Stage (Y1,Y2,O,G)

The ECM fan adjusts to 2nd stage CFM level, and the compressor full load solenoid valve is energized.

Fan Only

When the ECM control module receives a "G" call without a call for heating or cooling, the fan operates at 50% of the full load CFM level.

Thermostat Wiring / Fan Speed Notes

For two-stage compressor section units, wire as shown in the wiring diagram on the following page. For single stage units, jumper Y1 and Y2, and use the "CFM Y2" column in table 9b for determining jumper location. The ECM control board in the air handler is the thermostat connection point. Wire nut the thermostat wiring to the "pigtails" connected to the 1/4" spades on the ECM board.

Section 11: Controls

For dehumidification in cooling, cut the resistor at the "DEHUMIDIFY" LED. Use either the HUM terminal (reverse logic -- designed to be used with a humidistat) to lower the fan speed when dehumidification is needed, or if the HUM terminal is not connected (and the resistor is cut), the air handler will operate at a lower fan speed in cooling and normal fan speed in heating.

Figure 19: Lockout Board (Compr Section)





Figure 20: ECM Board (Air Handler Section)



Section 11: Controls


Table 11: MPD Air Handler Fan Speeds

Model Number	COOL Jumper	HEAT Jumper	ADJUST Jumper	High SPD CFM Y2			Low SPD CFM Y1			FAN G		
				.40"	.60"	.80"	.40"	.60"	.80"	.40"	.60"	.80"
RT024 with MPD024A Ships Set On: COOL Jumper A HEAT Jumper A ADJUST Jumper Norm	A	A	Norm	970	957	941	739	731	726	370	366	363
	B	B	Norm	895	884	874	688	674	652	344	337	326
	C	C	Norm	835	828	817	647	637	609	324	319	305
	D	D	Norm	807	803	788	623	604	579	312	302	290
	A	A	+	1009	997	985	860	849	806	430	425	403
	B	B	+	1012	991	982	783	775	763	392	388	382
	C	C	+	963	957	944	739	726	722	370	363	361
	D	D	+	924	914	901	708	704	687	354	352	344
RT036 with MPD036A Ships Set On: COOL Jumper C HEAT Jumper C ADJUST Jumper Norm	A	A	Norm	1556	1556	1508	1448	1448	1428	567	539	502
	B	B	Norm	1547	1547	1518	1239	1239	1227	476	433	407
	C	C	Norm	1312	1308	1308	1012	1006	1006	396	349	302
	D	D	Norm	1150	1145	1139	880	873	865	322	288	N/A
	A	A	+	1556	1556	1508	1566	1566	1518	674	633	619
	B	B	+	1547	1547	1518	1428	1428	1428	558	529	493
	C	C	+	1528	1520	1486	1156	1156	1156	450	404	377
	D	D	+	1317	1317	1317	1024	1020	1006	395	345	302
RT048 with MPD060B Change to: COOL Jumper C HEAT Jumper C ADJUST Jumper Norm	A	A	Norm	2180	2170	2116	1810	1810	1784	1157	1137	1137
	B	B	Norm	2015	2015	2004	1678	1678	1664	1087	1087	1045
	C	C	Norm	1710	1701	1693	1407	1407	1396	953	934	905
	D	D	Norm	1567	1567	1546	1318	1304	1274	911	989	962
RT060 with MPD060B Ships Set On: COOL Jumper B HEAT Jumper B ADJUST Jumper Norm	A	A	+	2243	2170	2116	1885	1860	1823	1289	1271	1253
	B	B	+	2232	2170	2105	1897	1873	1848	1215	1203	1191
	C	C	+	1937	1921	1914	1612	1612	1603	1032	1017	981
	D	D	+	1809	1795	1752	1493	1488	1467	1003	978	945

NOTES:

- Dehumidification mode can be enabled by cutting the jumper on the ECM board. When cut, cooling CFM is reduced by 15%, and heating/auxiliary heat CFM remains unchanged. **Example:** Model 036 with HEAT and COOL jumpers on C setting and ADJUST jumper on Norm setting would run at 1115 CFM with jumper cut, instead of 1308 CFM with jumper intact.
- Gray shaded areas are recommended settings. Other settings may be used, depending upon application. DO NOT cut dehumidification jumper if CFM setting will cause airflow to be below 250 CFM per ton on first stage, and below 325 CFM per ton on second stage. **Example:** Model 036 should not run below 750 CFM in first stage, or below 975 CFM in second stage.
- The COOL and HEAT jumpers should both be set at the same position. COOL controls heating and cooling airflow; HEAT controls electric heat airflow.
- Above CFM will be maintained up to 0.50" ESP for models MPD024 and 036, and up to 0.75" ESP for models MPD048 and 60.

Section 11: Controls



NOTES:

1. FACTORY INSTALLED JUMPER. REMOVE FOR USE WITH SOLENOID VALVE WITH END SWITCH. VERIFY THAT AIR HANDLER TRANSFORMER IS AT LEAST 50VA FOR UNITS WITHOUT WATER SOLENOID VALVE(S), OR 75VA FOR UNITS WITH WATER SOLENOID VALVE(S).
2. JUMPER INSTALLED=NORMAL; JUMPER REMOVED=TEST.
3. CIRCUIT BREAKERS ARE INSTALLED ON RESIDENTIAL MODELS ONLY.
4. LOOP PUMP WIRING HARNESS IS PROVIDED IN LOOP PUMP KIT.



Section 11: Wiring Diagrams - AH Electric Heat: MPD024-036 - 10kw

- C OUTDOOR UNIT CONTACTOR
- CB CIRCUIT BREAKER
- HS HEAT SEQUENCER
- LS LIMIT SWITCH
- P1 ACC HEAT CONTROL PLUG
- P4 ACC HEAT CONTROL PLUG
- P5 P B PLUG
- P6 P B CABLE PLUG
- P7 MTR CABLE PLUG
- P8 MTR PLUG
- P9 MTR CORD PLUG
- P10 MTR PWR CORD PLUG
- P11 MTR PWR CORD PLUG
- P12 PROXIMAL BOARD
- P13 LINE VOLTAGE TERMINAL BOARD
- P14 TRANSFORMER
- XTMR


MPD24,36 10 KW GE ECM
 FIELD WIRING PER LOCAL CODE
 12 GA TYPE 1015 600V TEW 105° C
 18 GA TYPE 1015 600V TEW 105° C
 18 GA TYPE 1015 600V TEW 105° C 24V
 LOW VOLTAGE FIELD WIRING

! WARNING:
 Switch circuit breaker to the OFF position before servicing the furnace.

ENERTECH
 E61CC0844 03 MARCH 2009




Section 11: Wiring Diagrams - AH Electric Heat: MPD042-072 - 10kw




- C OUTDOOR UNIT CONTACTOR
- CB CIRCUIT BREAKER
- HS HEAT SEQUENCER
- LS LIMIT SWITCH
- P1 ACC HEAT CONTROL PLUG
- P4 ACC HEAT PLUG
- P5 P B PLUG
- P6 MTR CABLE PLUG
- P7 MTR PLUG
- P8 MTR CORD PLUG
- P9 MTR PWR BOARD
- P10 MTR PWR CORD PLUG
- PB PROGRAM BOARD
- TB LINE VOLTAGE TERMINAL BOARD
- XTMR TRANSFORMER

MPD042.48.60 10 KW GE ECM
 FIELD WIRING PER LOCAL CODE
 12 GA TYPE 1015 600V TEW 105° C
 18 GA TYPE 1015 600V TEW 105° C
 18 GA TYPE 1015 600V TEW 105° C 24V
 LOW VOLTAGE FIELD WIRING



! WARNING:
 Switch circuit breaker to the OFF position before servicing the furnace.





ENERTECH

E61CC0811 09 MARCH 2009

Section 11: Wiring Diagrams - AH Electric Heat: MPD060-072 - 15kw


- C OUTDOOR UNIT CONTACTOR
- CB CIRCUIT BREAKER
- MS HEAT SENSORS
- LS HEAT SENSORS
- P5 ACC HEAT CONTROL PLUG
- P4 P B CABLE PLUG
- P7 MTR CABLE PLUG
- P8 MTR COORD PLUG
- P9 MTR COORD PLUG
- P10 PROGRAM BOARD
- PB LINE VOLTAGE TERMINAL BOARD
- XFMR TRANSFORMER

MPD42,48,60	15 KW GE ECM
FIELD WIRING PER LOCAL CODE	
12 GA TYPE 1015 600V TEW 105° C	
18 GA TYPE 1015 600V TEW 105° C	
18 GA TYPE 1015 600V TEW 105° C 24V	
LOW VOLTAGE FIELD WIRING	




! WARNING:

Switch circuit breaker to the OFF position before servicing the furnace.



ENERTECH
E61CC0813 09 MARCH 2009

Section 11: Wiring Diagrams - AH Electric Heat: MPD060-072 - 20kw



Section 12: Accessories

AP SMA PUMP SHARING MODULE

The pump sharing module, part number APS-MA, is designed to allow two units to share one flow center. With the APSMA module, either unit can energize the pump(s). Connect the units and flow center as shown in Figure 21, below. Figure 22 includes a schematic of the board. The module must be mounted in a NEMA enclosure or inside the unit control box. Local code supersedes any recommendations in this document.

Figure 21: APSMA Module Layout





Figure 22: APSMA Module Wiring Schematic



Section 13: Troubleshooting

PERFORMANCE CHECK

Heat of Extraction(HE)/Rejection(HR)

Record information on the Unit Start-up Form

Equipment should be in full load operation for a minimum of 10 minutes in either mode – **WITH THE HOT WATER GENERATOR TURNED OFF.**

1. Determine flow rate in gallons per minute
 - a. Check entering water temperature
 - b. Check entering water pressure
 - c. Check leaving water pressure

Once this information is recorded, find corresponding entering water temperature column in Specification Manual for unit. Find pressure differential in PSI column in Spec Manual. Then read the GPM column in Spec Manual to determine flow in GPM.

2. Check leaving water temperature of unit.
FORMULA: $GPM \times \text{water temp diff} \times 485$ (antifreeze) or 500 (fresh water) = HE or HR in BTU/HR

A 10% variance from Spec Manual is allowed. Always use the same pressure gauge & temperature measuring device. Water flow must be in range of Specification Manual. If system has too much water flow, performance problems should be expected

Section 13: Troubleshooting

A: UNIT WILL NOT START IN EITHER CYCLE

Thermostat	Set thermostat on heating and highest temperature setting. Unit should run. Set thermostat on cooling and lowest temperature setting. Unit should run. Set fan to On position. Fan should run. If unit does not run in any position, disconnect wires at heat pump terminal block and jump R, G, Y. Unit should run in heating. If unit runs, replace thermostat with correct thermostat only.
Loose or broken wires	Tighten or replace wires.
Blown Fuse/ Tripped Circuit Breakers	Check fuse size, replace fuse or reset circuit breaker. Check low voltage circuit breaker.
Low Voltage Circuit	Check 24 volt transformer. If burned out or less than 24 volt, replace. Before replacing, verify tap setting and correct if necessary.
Water Flow	If water flow is low (less than 3.5 GPM), unit will not start. Make sure Pump Module or solenoid valve is connected (see wiring diagram). Water has to flow through the heat exchanger in the right direction (see labels at water fitting connections) before the compressor can start. If water flow is at normal flow, use an ohmmeter to check if you get continuity at the flow switch. If no switch is open and flow is a normal flow, remove switch and check for stuck particles or bad switch.

B: UNIT RUNNING NORMAL, BUT SPACE TEMPERATURE IS UNSTABLE

Thermostat	Thermostat is getting a draft of cold or warm air. Make sure that the wall or hole used to run thermostat wire from the ceiling or basement is sealed, so no draft can come to the thermostat. Faulty Thermostat (Replace).
------------	--

C: NO WATER FLOW

Pump Module	Make sure Pump Module is connected to the control box relay (check all electrical connections). For non-pressurized systems, check water level in Pump Module. If full of water, check pump. Close valve on the pump flanges and loosen pump. Take off pump and see if there is an obstruction in the pump. If pump is defective, replace. For pressurized systems, check loop pressure. Repressurize if necessary. May require re-flushing if there is air in the loop.
Solenoid valve	Make sure solenoid valve is connected. Check solenoid. If defective, replace.

D: IN HEATING OR COOLING MODE, UNIT OUTPUT IS LOW

Water	Water flow & temperature insufficient.
Airflow	Check speed setting, check nameplate or data manual for proper speed, and correct speed setting. Check for dirty air filter—Clean or replace. Restricted or leaky ductwork. Repair.
Refrigerant charge	Refrigerant charge low, causing inefficient operation. Make adjustments only after airflow and water flow are checked.
Reversing valve	Defective reversing valve can create bypass of refrigerant to suction side of compressor. Switch reversing valve to heating and cooling mode rapidly. If problem is not resolved, replace valve. Wrap the valve with a wet cloth and direct the heat away from the valve. Excessive heat can damage the valve. Always use dry nitrogen when brazing. Replace filter/drier any time the circuit is opened.

E: IN HEATING OR COOLING MODE, UNIT OUTPUT IS LOW

Heat pump will not cool but will heat. Heat pump will not heat but will cool.	Reversing valve does not shift. Check reversing valve wiring. If wired wrong, correct wiring. If reversing valve is stuck, replace valve. Wrap the valve with a wet cloth and direct the heat away from the valve. Excessive heat can damage the valve. Always use dry nitrogen when brazing. Replace filter/drier any time the circuit is opened.
Water heat exchanger	Check for high-pressure drop, or low temperature drop across the coil. It could be scaled. If scaled, clean with condenser coil cleaner.
System undersized	Recalculate conditioning load.

F: WATER HEAT EXCHANGER FREEZES IN HEATING MODE

Water flow	Low water flow. Increase flow. See F. No water flow.
Flow Switch	Check switch. If defective, replace.

G: EXCESSIVE HEAD PRESSURE IN COOLING MODE

Inadequate water flow	Low water flow, increase flow.
-----------------------	--------------------------------

Section 13: Troubleshooting

H: EXCESSIVE HEAD PRESSURE IN HEATING MODE

Low air flow	See E: Noisy blower and low air flow.
--------------	---------------------------------------

I: AIR COIL FREEZES OVER IN COOLING MODE


Air flow	See E: Noisy blower and low air flow.
Blower motor	Motor not running or running too slow. Motor tripping off on overload. Check for overheated blower motor and tripped overload. Replace motor if defective.
Panels	Panels not in place.
Low air flow	See E: Noisy blower and low air flow.

J: WATER DRIPPING FROM UNIT

Unit not level	Level unit.
Condensation drain line plugged	Unplug condensation line.
Water sucking off the air coil in cooling mode	Too much airflow. Duct work not completely installed. If duct work is not completely installed, finish duct work. Check static pressure and compare with air flow chart in spec manual under specific models section. If ductwork is completely installed it may be necessary to reduce CFM.
Water sucking out of the drain pan	Install an EZ-Trap or P-Trap on the drain outlet so blower cannot suck air back through the drain outlet.

Section 13: Troubleshooting


O: COMPRESSOR WON'T START



A: Check all terminals, wires & connections for loose or burned wires and connections. Check contactor and 24 Volt coil. Check capacitor connections & check capacitor with capacitor tester.

B: If ohm meter reads 0 (short) resistance from C to S, S to R, R to C or from any one of these terminals to ground (shorted to ground), compressor is bad.

P: COMPRESSOR WON'T PUMP CHART



Section 13: Troubleshooting

Table 12a: Model 024 Operational Data - Cooling Mode

Troubleshooting Data - Cooling Mode, Full Load Operation*											
Model	Entering Water Temp., DB deg. F	Entering Air Temp., DB deg. F	GPM/ton	Liquid Line Press., psi	Suction Line Press., psi	Subcooling	Superheat	Water Temp. Rise, deg. F	Air Temp. Drop, deg F		
									375 CFM/ton	400 CFM/ton	425 CFM/ton
024	50	70 - 85	1.5	212 - 232	127 - 147	20 - 24	12 - 16	20 - 24	24 - 28	22 - 26	21 - 25
			2.25	188 - 208	127 - 147	16 - 20	13 - 17	13 - 17			
			3	176 - 196	126 - 146	13 - 17	13 - 17	9 - 13			
	60		1.5	254 - 274	129 - 149	20 - 24	12 - 16	20 - 24	24 - 28	22 - 26	21 - 25
			2.25	230 - 250	129 - 149	15 - 19	12 - 16	13 - 17			
			3	218 - 238	128 - 148	13 - 17	12 - 16	9 - 13			
	70		1.5	296 - 316	131 - 151	20 - 24	11 - 15	20 - 24	23 - 27	22 - 26	20 - 24
			2.25	272 - 292	130 - 150	16 - 20	12 - 16	12 - 16			
			3	260 - 280	130 - 150	13 - 17	12 - 16	9 - 13			
	80		1.5	338 - 358	133 - 153	20 - 24	11 - 15	19 - 23	23 - 27	21 - 25	20 - 24
			2.25	314 - 334	132 - 152	16 - 20	11 - 15	12 - 16			
			3	302 - 322	132 - 152	14 - 18	11 - 15	8 - 12			
90	1.5	380 - 400	135 - 155	22 - 26	11 - 15	19 - 23	22 - 26	21 - 25	19 - 23		
	2.25	356 - 376	134 - 154	17 - 21	11 - 15	12 - 16					
	3	344 - 364	134 - 154	15 - 19	11 - 15	8 - 12					

Table 12b: Model 036 Operational Data - Cooling Mode

Troubleshooting Data - Cooling Mode, Full Load Operation*											
Model	Entering Water Temp., DB deg. F	Entering Air Temp., DB deg. F	GPM/ton	Liquid Line Press., psi	Suction Line Press., psi	Subcooling	Superheat	Water Temp. Rise, deg. F	Air Temp. Drop, deg F		
									375 CFM/ton	400 CFM/ton	425 CFM/ton
036	50	70 - 85	1.5	220 - 240	117 - 137	23 - 27	19 - 23	19 - 23	20 - 24	19 - 23	18 - 22
			2.25	198 - 218	114 - 134	20 - 24	24 - 28	12 - 16			
			3	187 - 207	112 - 132	18 - 22	25 - 29	9 - 13			
	60		1.5	260 - 280	121 - 141	22 - 26	16 - 20	18 - 22	20 - 24	19 - 23	18 - 22
			2.25	238 - 258	118 - 138	19 - 23	20 - 24	11 - 15			
			3	227 - 247	116 - 136	17 - 21	22 - 26	8 - 12			
	70		1.5	301 - 321	125 - 145	21 - 25	13 - 17	18 - 22	20 - 24	19 - 23	18 - 22
			2.25	279 - 299	122 - 142	18 - 22	17 - 21	11 - 15			
			3	268 - 288	120 - 140	17 - 21	19 - 23	8 - 12			
	80		1.5	341 - 361	129 - 149	21 - 25	10 - 14	18 - 22	20 - 24	19 - 23	17 - 21
			2.25	320 - 340	126 - 146	18 - 22	14 - 18	11 - 15			
			3	308 - 328	124 - 144	16 - 20	16 - 20	8 - 12			
90	1.5	382 - 402	133 - 153	20 - 24	7 - 11	17 - 21	20 - 24	19 - 23	17 - 21		
	2.25	360 - 380	130 - 150	17 - 21	11 - 15	11 - 15					
	3	349 - 369	128 - 148	16 - 20	13 - 17	7 - 11					

* Pressures are for reference only--Do not use for charging. Preferred charging method is using approach temperatures in cooling.

Section 13: Troubleshooting

Table 12c: Model 048 Operational Data - Cooling Mode

Troubleshooting Data - Cooling Mode, Full Load Operation*											
Model	Entering Water Temp., DB deg. F	Entering Air Temp., DB deg. F	GPM/ton	Liquid Line Press., psi	Suction Line Press., psi	Subcooling	Superheat	Water Temp. Rise, deg. F	Air Temp. Drop, deg F		
									375 CFM/ton	400 CFM/ton	425 CFM/ton
048	50	70 - 85	1.5	213 - 233	127 - 147	10 - 14	11 - 15	20 - 24	23 - 27	21 - 25	20 - 24
			2.25	186 - 206	127 - 147	5 - 9	12 - 16	13 - 17	23 - 27	21 - 25	20 - 24
			3	172 - 192	127 - 147	3 - 7	12 - 16	9 - 13	23 - 27	21 - 25	20 - 24
	60		1.5	256 - 276	129 - 149	12 - 16	10 - 14	20 - 24	22 - 26	21 - 25	19 - 23
			2.25	229 - 249	129 - 149	8 - 12	11 - 15	12 - 16	22 - 26	21 - 25	19 - 23
			3	215 - 235	129 - 149	6 - 10	11 - 15	9 - 13	22 - 26	21 - 25	20 - 24
	70		1.5	299 - 319	131 - 151	15 - 19	10 - 14	19 - 23	22 - 26	20 - 24	19 - 23
			2.25	273 - 293	131 - 151	11 - 15	11 - 15	12 - 16	22 - 26	20 - 24	19 - 23
			3	259 - 279	131 - 151	8 - 12	11 - 15	9 - 13	22 - 26	21 - 25	19 - 23
	80		1.5	343 - 363	133 - 153	18 - 22	10 - 14	19 - 23	21 - 25	20 - 24	19 - 23
			2.25	316 - 336	133 - 153	13 - 17	10 - 14	12 - 16	22 - 26	20 - 24	19 - 23
			3	302 - 322	133 - 153	11 - 15	11 - 15	8 - 12	22 - 26	20 - 24	19 - 23
90	1.5	386 - 406	135 - 155	20 - 24	9 - 13	19 - 23	21 - 25	19 - 23	18 - 22		
	2.25	359 - 379	135 - 155	16 - 20	10 - 14	12 - 16	21 - 25	20 - 24	18 - 22		
	3	345 - 365	134 - 154	14 - 18	10 - 14	8 - 12	21 - 25	20 - 24	18 - 22		

Table 12d: Model 060 Operational Data - Cooling Mode

Troubleshooting Data - Cooling Mode, Full Load Operation*											
Model	Entering Water Temp., DB deg. F	Entering Air Temp., DB deg. F	GPM/ton	Liquid Line Press., psi	Suction Line Press., psi	Subcooling	Superheat	Water Temp. Rise, deg. F	Air Temp. Drop, deg F		
									375 CFM/ton	400 CFM/ton	425 CFM/ton
060	50	70 - 85	1.5	202 - 222	120 - 140	15 - 19	14 - 18	19 - 23	21 - 25	20 - 24	18 - 22
			2.25	179 - 199	119 - 139	10 - 14	15 - 19	12 - 16			
			3	168 - 188	118 - 138	8 - 12	16 - 20	9 - 13			
	60		1.5	237 - 257	122 - 142	16 - 20	12 - 16	19 - 23	21 - 25	19 - 23	18 - 22
			2.25	215 - 235	121 - 141	11 - 15	13 - 17	12 - 16			
			3	203 - 223	121 - 141	9 - 13	14 - 18	8 - 12			
	70		1.5	277 - 297	124 - 144	17 - 21	12 - 16	19 - 23	20 - 24	19 - 23	18 - 22
			2.25	254 - 274	124 - 144	13 - 17	13 - 17	12 - 16			
			3	242 - 262	123 - 143	10 - 14	14 - 18	8 - 12			
	80		1.5	320 - 340	126 - 146	18 - 22	11 - 15	18 - 22	20 - 24	18 - 22	17 - 21
			2.25	297 - 317	126 - 146	14 - 18	13 - 17	11 - 15			
			3	285 - 305	125 - 145	12 - 16	14 - 18	8 - 12			
90	1.5	366 - 386	128 - 148	19 - 23	12 - 16	18 - 22	19 - 23	18 - 22	17 - 21		
	2.25	344 - 364	128 - 148	15 - 19	13 - 17	11 - 15					
	3	332 - 352	127 - 147	12 - 16	14 - 18	8 - 12					

* Pressures are for reference only--Do not use for charging. Preferred charging method is using approach temperatures in cooling.

Section 13: Troubleshooting

Table 12e: Model 072 Operational Data - Cooling Mode

Troubleshooting Data - Cooling Mode, Full Load Operation*											
Model	Entering Water Temp., DB deg. F	Entering Air Temp., DB deg. F	GPM/ton	Liquid Line Press., psi	Suction Line Press., psi	Subcooling	Superheat	Water Temp. Rise, deg. F	Air Temp. Drop, deg F		
									375 CFM/ton	400 CFM/ton	425 CFM/ton
072	50	70 - 85	1.5	200 - 220	113 - 133	13 - 17	16 - 20	18 - 22	19 - 23	17 - 21	16 - 20
			2.25	179 - 199	112 - 132	10 - 14	18 - 22	11 - 15	19 - 23	17 - 21	16 - 20
			3	168 - 188	111 - 131	8 - 12	20 - 24	8 - 12	19 - 23	17 - 21	16 - 20
	60		1.5	236 - 256	115 - 135	14 - 18	14 - 18	17 - 21	19 - 23	17 - 21	16 - 20
			2.25	214 - 234	114 - 134	11 - 15	16 - 20	11 - 15	19 - 23	17 - 21	16 - 20
			3	203 - 223	113 - 133	9 - 13	18 - 22	8 - 12	18 - 22	17 - 21	16 - 20
	70		1.5	274 - 294	118 - 138	15 - 19	13 - 17	17 - 21	18 - 22	17 - 21	16 - 20
			2.25	253 - 273	117 - 137	11 - 15	15 - 19	11 - 15	18 - 22	17 - 21	16 - 20
			3	242 - 262	116 - 136	10 - 14	16 - 20	7 - 11	18 - 22	17 - 21	16 - 20
	80		1.5	316 - 336	120 - 140	16 - 20	12 - 16	17 - 21	18 - 22	17 - 21	15 - 19
			2.25	295 - 315	119 - 139	12 - 16	14 - 18	11 - 15	18 - 22	17 - 21	15 - 19
			3	284 - 304	118 - 138	10 - 14	15 - 19	7 - 11	18 - 22	16 - 20	15 - 19
90	1.5	362 - 382	123 - 143	17 - 21	11 - 15	17 - 21	17 - 21	16 - 20	15 - 19		
	2.25	341 - 361	121 - 141	13 - 17	13 - 17	10 - 14	17 - 21	16 - 20	15 - 19		
	3	329 - 349	121 - 141	11 - 15	14 - 18	7 - 11	17 - 21	16 - 20	15 - 19		

* Pressures are for reference only--Do not use for charging. Preferred charging method is using approach temperatures in cooling.

Section 13: Troubleshooting

Table 13: Refrigeration Troubleshooting

System Faults	Mode	Discharge Pressure	Suction Pressure	Superheat	Subcooling	Air TD	Water TD	Compressor Amps
Under Charge	Heat	Low	Low	High	Low	Low	Low	Low
	Cool	Low	Low	High	Low	Low	Low	Low
Over Charge	Heat	High	High/Normal	Normal	High	High	Normal	High
	Cool	High	High/Normal	Normal	High	Normal	High	High
Low Air Flow	Heat	High	High/Normal	Normal	High/Normal	High	Low	High
	Cool	Low	Low/Normal	Low	Normal	High	Low	High/Normal
Low Source Water Flow	Heat	Low	Low/Normal	Low	Normal	High	Low	High/Normal
	Cool	High	High/Normal	Normal	High/Normal	High	Low	High
Low Load Water Flow	Heat	High	High/Normal	Normal	High/Normal	High	Low	High
	Cool	Low	Low/Normal	Low	Normal	High	Low	High/Normal
Restricted TXV	Heat	High	Low	High	High	Low	Low	Low
	Cool	High	Low	High	High	Low	Low	Low
TXV Stuck Open	Heat	Low	High/Normal	Low	Low	Low	Low	High
	Cool	Low	High/Normal	Low	Low	Low	Low	High
Inadequate Compression	Heat	Low	High	High/Normal	Low/Normal	Low	Low	Low
	Cool	Low	High	High/Normal	Low/Normal	Low	Low	Low

Section 14: Forms - Troubleshooting


Customer/Job Name: _____ Date: _____

Model #: _____ Serial #: _____

Antifreeze Type: _____

HE or HR = GPM x TD x Fluid Factor
(Use 500 for water; 485 for antifreeze)

SH = Suction Temp. - Suction Sat.
SC = Disch. Sat. - Liq. Line Temp.



Cut along this line

EQUIPMENT START-UP FORM

Customer Name: _____

Customer Address: _____

Model #: _____ Serial #: _____

Dealer Name: _____

Distributor Name: _____ Start-up Date: _____

Loop Type: Open Closed (Circle One)										
Flow Rate	Cooling		Heating		Unit Electrical Data		Cooling		Heating	
Source Water Pressure In		PSI		PSI	Line Voltage			V		
Source Water Pressure Out		PSI		PSI	Total Unit Amps			A		A
Source Water Pressure Drop		PSI		PSI	Compressor Amps			A		A
Flow Rate		GPM		GPM	Wire Size			GA		
*Check pressure drop chart for GPM					Circuit Breaker Size			A		

Source Water Temp. Difference	Cooling		Heating	
Source Water Temperature In		°F		°F
Source Water Temperature Out		°F		°F
Source Water Temperature Difference		°F		°F
Heat of Rejection/Extraction	Cooling		Heating	
Heat of Rejection		BTU/HR		
Heat Of Extraction				BTU/HR

Heat of Extraction/Rejection = GPM X Water Temp. Difference X 500 (Water - Open Loop)
 Heat of Extraction/Rejection = GPM X Water Temp. Difference X 485 (Water & Antifreeze - Closed Loop)

Load Water Temp. Difference	Cooling		Heating	
Load Water Temperature In		°F		°F
Load Water Temperature Out		°F		°F
Load Water Temperature Difference		°F		°F

Air Temperature Difference	Cooling	Heating
Supply Air Temperature	°F	°F
Return Air Temperature	°F	°F
Air Temp. Difference	°F	°F

*Confirm auxiliary heaters are de-energized for the above readings.

Auxiliary Heat Operation Only	Heating
Supply Air Temperature	°F
Return Air Temperature	°F
Air Temp. Difference	°F

Auxiliary Heat Electrical Data	Heating
Line Voltage	V
Total Amperage (Full kW - All Stages)	A
Wire Size	GA
Breaker Size	A

CFM = (Watts X 3.413) ÷ (Air Temp. Difference X 1.08)
 Watts = Volts X Auxiliary Heater Amps

Cut along this line

Installer/Technician: _____ Date: _____

Equipment Start-Up Process

Check the following before power is applied to the equipment

Caution: Do not start-up the unit until the new structure is ready to be occupied

Electrical:

- Geothermal unit high voltage wiring is installed correctly
- Geothermal unit high voltage wiring and breaker are the correct size
- Auxiliary electric heaters are wired and installed correctly
- Circulating pumps are wired and fused (if necessary) correctly
- Low voltage wiring is correct and completely installed

Plumbing:

- Pipe and pump sizes are correct
- Air is purged from all lines
- Antifreeze is installed
- All valves are open, including those on the flow center
- Condensate is trapped and piped to the drain

Ductwork:

- Filter is installed and clean
- Packaging is removed from the blower assembly
- Blower turns freely
- Canvas connections installed on supply plenum & return drop

Equipment Start-Up

1. Energize geothermal unit with high voltage.
2. Set the thermostat to "Heat" or "Cool." Adjust set point to energize the unit. System will energize after delays expire (typically a five minute delay).
3. Check water flow with a flow meter (non-pressurized) or pressure drop conversion (pressurized). Pressure drop tables must be used to convert the pressure drop to GPM. The pressure drop can be obtained by checking water pressure in and water pressure out at the P/T ports.
4. Check the geothermal unit's electrical readings listed in the Unit Electrical Data table.
5. Check the source water temperature in and out at the P/T ports (use insertion probe). Allow 10 minutes of operation before recording temperature drop.
6. Calculate the heat of extraction or heat of rejection.
7. Check the temperature difference of the load coax (water-to-water) or air coil (water-to-air). P/T ports are recommended for use on the load side, but the line temperatures can be used to check the temperature difference.
8. Change the mode of the thermostat and adjust the set point to energize the unit. Check the data in opposite mode as the previous tests. Amp draws as well as temperature differences and flow rate should be recorded.
9. Check auxiliary heat operation by adjusting the thermostat set point 5°F above the room temperature in "Heat" mode or set thermostat to "Emergency." Record voltage, amperage, and air temperature difference.



WARRANTY ORDER & CLAIM

PHONE: 618.664.9010 FAX: 618.664.4597 EMAIL: WARRANTY@ENERTECHGEO.COM

ALL WARRANTY REGISTRATIONS SHOULD BE SUBMITTED WITHIN 10 DAYS OF INSTALLATION

COMPANY NAME _____ (Form submitter) DATE _____

PHONE _____ FAX _____ EMAIL _____

ORDERED BY _____ JOB NAME/PO # _____

UNIT Model # _____ Serial # _____

INSTALL DATE² _____ FAILURE DATE _____

SHIP TO _____ HOMEOWNER ADDRESS _____
(if different than company)

Required if claim is for defective flow center

FLOW CENTER MODEL # _____ FLOW CENTER SERIAL # _____

FAILURE CODES, DESCRIPTION AND LABOR REIMBURSEMENT MUST BE FOUND IN WARRANTY MANUAL

FAILURE CODE	DESCRIPTION	DOA HOURS	OR FLAT RATE
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

SERVICE LABOR ALLOWANCE NO YES DOA

DO YOU NEED PARTS ORDERED? NO YES

(If no, and replacement was purchased from another vendor, attach copy of bill if reimbursement is needed.)

OTHER NOTES _____

FOR ENERTECH USE ONLY

SRO# _____ CREDIT MEMO# _____

1) See warranty coverage summary sheet for labor allowances, conditions and exclusions, etc. **2)** Warranty start date is ship date from Enertech facility unless proof of startup is presented. **3)** Outsourced warranty replacement parts will be reimbursed in the form of credit for the part only. Credit will be no more than the standard equivalent part cost through Enertech. **4)** Factory pre-approval is required for anything outside the scope of this document. **5)** Fuses, hose kits and items not mentioned on Warranty Coverage Summary are not covered under this program.



WARRANTY REGISTRATION

PHONE: 618.664.9010 FAX: 618.664.4597 EMAIL: WARRANTY@ENERTECHGEO.COM

ALL WARRANTY REGISTRATIONS SHOULD BE SUBMITTED WITHIN 10 DAYS OF INSTALLATION

MODEL NUMBER _____ SERIAL NUMBER _____ BRAND _____
 DATE OF SALE _____ DELIVERY DATE _____ INSTALL DATE _____

APPLICATION

- RESIDENTIAL NEW CONSTRUCTION RESIDENTIAL GEO REPLACEMENT RESIDENTIAL RETROFIT
 MULTI-FAMILY (CONDO/TOWNHOME/MULTI-PLEX) COMMERCIAL OTHER _____

USE

- SPACE CONDITIONING DOMESTIC WATER HEATING RADIANT HEAT SWIMMING POOL SNOW MELT
 OTHER _____

Note: Check all that apply

SOURCE

- CLOSED LOOP (HORIZONTAL, VERTICAL, POND/LAKE) OPEN LOOP (WELL WATER) OTHER _____

SUPPLEMENTAL / EMERGENCY

- NONE ELECTRIC GAS PROPANE OIL WOOD OTHER _____

PURCHASER-USER _____ PHONE _____
 ADDRESS _____ CITY _____ STATE/PROV _____
 POSTAL CODE _____ EMAIL (OPTIONAL) _____

WE HAVE SUPERVISED THE INSTALLATION AND START-UP IN ACCORDANCE WITH ENERTECH MANUFACTURING, LLC. INSTALLATION INSTRUCTIONS.

THIS UNIT IS PERFORMING SATISFACTORILY NOT SATISFACTORILY, IF NOT EXPLAIN _____

TO THE BEST OF MY KNOWLEDGE THE ABOVE INFORMATION IS ACCURATE AND I REQUEST THE WARRANTY TO BE PUT INTO EFFECT.

DEALER (INSTALLER) _____ DATE _____
 CUSTOMER / END USER _____ DATE _____
 DEALER (INSTALLER) EMAIL _____

MAIL THIS FORM TO:
ENERTECH GLOBAL LLC
2506 SOUTH ELM STREET
GREENVILLE, IL 62246

FAX THIS FORM TO:
ENERTECH GLOBAL LLC
618.664.4597

OR REGISTER ONLINE AT WWW.ENERTECHGEO.COM