FOA Separated combustion

FSA Cayenne™ residential models

Flexible offerings for multiple unit heater applications



our features, your benefits.



eparated combustion, uses a two pipe system to eliminate indoor contaminates from entering the heat exchanger compartment.

FOA unit heaters only

ubular heat exchangers made of aluminized steel provide resistance to corrosion and oxidation. Easy to clean.



Easy Installation and Service

- Available in natural gas or propane
- Hanging brackets provided on the 30, 45, 60 and 75 models
- Hinged door with burner view port
- Easy to clean in-shot burners
- Self diagnostic board with indicator lights

Efficiency & Safety

Prior to ignition:

- Unit heater purges heat exchanger of any remaining exhaust gases
- Safety pressure switch checks for proper operating pressures

Flexibility & Quality

- Heat exchanger has been laboratory life-cycle tested
- 2 years limited warranty on parts
- 10 years limited warranty on heat exchanger

irect drive propeller fans are dynamically balanced for quiet, smooth operation.



FOAIFSA Series Series



Additional Features:

Power Exhaust System with sealed flue collector allows for vertical or horizontal venting up to 25-40 feet

Safe direct spark ignition occurs only when thermostat calls for heat. No standing pilot light.

FSA Cayenne™ Low Profile Unit Heater



- Great for garages
- Residential Low profile unit
- Wiring junction box is located inside the unit cabinet and self-diagnostic board with LED display improves troubleshooting.

FOA Separated Combustion Unit Heater

- Mostly used in light commercial and green houses applications (on selected models)
- Introduces clean combustible outside air when required
- Wiring junction box is located outside the unit
- Optional concentric venting kit and additional vent pipe available



om custom options. sizes.

FOA N 75

SERIES

FOA: Separated combustion unit heaters

FSA: Cayenne Unit Heaters

GAS

N: natural gas P: propane

Note: All unit heaters are 115V/1ph/60Hz

Nominal Gas Heat Input

FSA:

30, 45, 60, 75

FOA:

45, 60, 75, 100, 125, 150, 200, 250, 300

Recommended Sizing Guide						
Unit	Application					
FSA 30	l to 1.5 car garage					
FOA/FSA 45	2 to 2.5 car garage					
FOA 60	3 to 3.5 car garage					
FOA/FSA 75-125	Uninsulated or larger detached garage					

Mounting Clearance [in]					
Тор	I				
Bottom	0				
Access Side	18				
Side	I				
Back	18				



dimensions. specifications.

FSA m	30	45	60	75	
Thermal efficiency [%]			81	80	80
	Air volume [CFM]	536	750	830	950
Air throw at 8 foot mounting height [ft]			25	40	40
Temperature rise [°F]			45	55	60
Recommended mounting height *[ft]			10	12	12
Number of propeller fans			I	I	I
**Flue connection size [in]			3	4	4
Gas connection size NPT [in]			1/2	1/2	1/2
Shipping weight [lbs]			63	87	91
	Horsepower	1/20	1/20	1/8	1/8
Fan motor data	AMPS @ 115 V / 1 PH. / 60 Hz	1.7	1.7	4.1	4.1
	RPM	1,650	1,650	1,075	1,075
Depth [in] 18 1		1/2			
Width [in] 25			25		
	Height [in] 12			7	







^{**}Diameter of round pipe - adaptor furnished with heater

FOA m	odel size gas input [MBTUH]	45	60	75	100	125	*150	*200	*250	*300
	Thermal efficiency: NG [%]	81	81	80	81	81	80	82	81	80
	Thermal efficiency: LPG [%]	81	81	80	81	81	81	80	82	81
	Air volume [CFM]	750	830	950	2435	2435	2955	2955	5215	5215
Air Th	nrow at 8 ft • Mounting Height [ft]	25	40	40	50	50	80	80	100	100
Recommended mounting height [ft]		10	12	12	20	20	20	20	30	30
Number of propeller fans		1	I	I	I	I	I	I	2	2
Shipping weight [lbs]		84	100	104	188	204	261	266	307	323
Fan motor data	Horsepower	1/20	1/8	1/8	1/8	1/8	1/8	1/8	1/8	1/8
	AMPS @ 115 V / 1 PH. / 60 Hz	1.7	4.1	4.1	2.7	2.7	2.7	2.7	2.7	2.7
	RPM	1,650	1,075	1,075	1,075	1,075	1,075	1,075	1,075	1,075
Combustion air size [in]		3	4	4	4	4	4	4	4	4
	**Flue connection size [in]	3	4	4	5	5	5	5	5	6
Gas connection size NPT [in]		1/2	1/2	1/2	1/2	1/2	1/2	1/2	3/4	3/4
	Depth [in]	1 18 1/2 32 3/8								
	Width [in]		26	26 36 1/2						
Height [in]		12		17	21 27 39			19		

^{*}Sizes are not approved for residential application

^{*} To bottom of unit

^{**}Diameter of round pipe - adaptor furnished with heater

unit heater comparison.

Series	FSA Series	FOA Series	SEP Series	HED Series		
Description	Residential unit heater: For garages and small greenhouses	Light commercial unit heater: For light commercial, residential and warehouses	Commercial unit heater and duct furnace: For commercial and warehouses (SEP: unit heater. HED: duct furnace)			
Heat Input	[MTUH]	residential and waremouses	(SELL ATTICATION	TIED. ddet idiridee)		
30	•					
45	•	•				
60	•	•				
75	•	•		•		
100		•	•	•		
115			•			
125		•		•		
145			•			
150		۸		•		
175			•			
200		۸	•	•		
230			•			
250		۸	•	•		
300		^	•	•		
345			•			
400 Fuel			•			
Natural Gas	•	•	•	•		
Liquid Propane	0	0	0			
Heat Exchanger						
Aluminized Steel	•	•	•	•		
Stainless Steel			•	•		
Separated Combustion		•				

[•] available as a standard, factory installed

available from-factory and as a kit

[^] sizes are not approved for residential application

Advanced Distributor Products

making your business easier, each step of the way

ADP is one of the world's largest residential evaporator coil manufacturers.

We also offer high efficiency air handlers and easy-to-install unit heaters. Our primary purpose is to support each individual distributor in creating their own unique way of doing business.

Innovative Solutions We leverage our products and expertise to tailor innovative

solutions for each individual customer.

Superior Quality Our production system is ISO 9001:2000 certified and is supported

by an ETL calibrated laboratory. We strive to manufacture the

highest quality products in the marketplace.

Dependable Delivery We have industry leading cycle-times and carry a strategic inventory

of our most popular models to meet seasonal demands.

Profitable Partnership Our team recognizes the value of long-term relationships. We

have an "easy-to-do-business" heritage and acknowledge that each

customer is different.



innovative solutions.

presenting the ADP product line.



© by Advanced Distributor Products. All rights reserved. We reserve the right to make changes in specification, at any time, without notice and without liability to purchasers or owners of previously sold equipment.

Proudly distributed by:



SL-FOAFSA-02 February, 2009

2175 West Park Place Boulevard Stone Mountain, Georgia 30087 www.adpnow.com adp.feedback@adpnow.com